POLYKEN®

Contributes toward LEED® Certification Credits.

339

Premium UL181A& B-FX Foil Tape



Backing: Printed 2 mil Foil

Adhesive: Cold weather Acrylic

Liner: Unbleached Natural Kraft Paper

Colors: Aluminum

Specifications: UL181A & UL181B-FX Listed

Standard Sizes: 2.5" x 60Yd, 72mm x 55m

Applications

- Permanently seals seams in fiberglass duct board and flexible ducts for HVAC systems
- Suitable for use on rigid sheet metal ducts
- Durable seal for dryer ventilation

Features & Benefits

- Aggressive cold weather acrylic adhesive
- New unbleached kraft release liner
- UL181A & B-FX Listed
- Low VOC Content
- Superior performance in all climate conditions
- Mold & Mildew Resistant
- Reduced environmental impact
- Meets code requirements and can contribute toward requirements for EA Credit 1 (Optimize Energy Performance) under LEED®
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Physical Properties

	Standard UOM	Metric UOM	Test Method
Total Thickness	4.8 mils	121.92 mic	ASTM D-1000
Adhesion to Steel	68 oz/in	7.44 N/cm	PSTC-101
Adhesion to Backing	60 oz/in	6.57 N/cm	PSTC-101
Tensile Strength	27 lb/in	47.28 N/cm	ASTM D-1000
Operating Temperature	-20 to 325° F	-29 to 163°C	
Application Temperature	-10 to 200° F	4 to 93° C	
Flame Spread	3		
Smoke Developed	0		
VOC Content	<30 g/L		

Recommended Storage Conditions: 40-60% Humidity, 60ºF - 80ºF
Standard Shelf Life (at 25C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.

BERRY PLASTICS CORPORATION AND SUBSIDIARIES
LEADERSHIP BY DESIGN

25 Forge Pkwy Franklin, MA 02038
1-800-343-7875 Fax 1-800-328-4822
www.berryplastics.com

Nijverheidsstraat 10
2260 Oevel (Westerlo) Belgium
32-014-722500 Fax 32-014-722570
8/13/12