

## HIGH PERFORMANCE GRADE VERY HIGH TEMPERATURE INDUSTRIAL MASKING TAPE

### TYPICAL APPLICATIONS

- Designed for today's high tech transportation industry (auto, coaches, buses and marine)
- Metal preparation, painting, coating and gel coat masking
- EPDM, rubber insulation protection

### ADVANTAGES AND BENEFITS

- No adhesive residue
- Excellent quick stick
- Clean, flat edges
- Excellent adhesion to metals, rubber, plastics and fiberglass
- Strips cleanly with no residue or paint flake after baking and extended application periods
- Excellent adhesion to tape backing and masking papers
- Smooth unwind

### CONSTRUCTION

Overall Grade/Function: High Performance

Backing: Fine structured crepe paper

Adhesive: Rubber-based



### COLOR(S)



Natural (NAT)

### STANDARD WIDTH(S)

18 mm 24 mm 36 mm 48 mm 55 m

Contact your Shurtape sales representative for other available sizes.

### STANDARD LENGTH(S)

### PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	25 lbs/in width	43.8 N/10 mm
Adhesion to Stainless Steel	39 oz/in width	4.27 N/10 mm
Thickness	6.3 mils	0.16 mm
Elongation	11%	11%
Service Temperature Range	45 F to 350 F	7 C to 163 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

### APPLICABLE STANDARDS

ASTM D 6123/D 6123M-97 (2012), Type I

### STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

\*Shurtape® is a registered trademark of Shurtape Technologies, LLC

Form# TDS-CF-740-08/20/2014