

INDUSTRIAL ABATEMENT POLYETHYLENE/CLOTH DUCT TAPE

TYPICAL APPLICATIONS

- Holding poly-sheeting in the asbestos/mold remediation industry

ADVANTAGES AND BENEFITS

- High adhesion and tack
- Does not twist or curl off of roll
- Excellent cold weather performance

CONSTRUCTION

Overall Grade/Function: Industrial Abatement
Backing: Polyethylene/film with a cloth carrier
Adhesive: Blended rubber

COLOR(S)

 Metallic Silver (MSL)

STANDARD WIDTH(S)

48 mm 72 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.



PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	27 lbs/in width	47.3 N/10 mm
Adhesion to Stainless Steel	53 oz/in width	5.80 N/10 mm
Thickness	10.5 mils	0.27 mm
Elongation	20%	20%
Service Temperature Range	25 F to 200 F	-4 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.