

# Silwipe 25

## Low VOC Wipe Solvent Cleaner Product Data Sheet



PO Box 9  
Tucker, GA 30084  
800-886-8240 • 770-621-8240  
[www.ecolink.com](http://www.ecolink.com)  
email: [info@ecolink.com](mailto:info@ecolink.com)

### Description

Silwipe 25 provides the future of environmentally sound industrial maintenance to your workplace today. This low VOC formula make use of the latest innovations in solvent chemistry resulting in a high purity, no-residue, fast dry formula.

Use Silwipe 25 to clean metal, plastic, and composite surfaces. Unlike high VOC solvents such as MEK, citrus terpenes, and n-propyl bromide, Silwipe 25 is able to perform a variety of cleaning jobs without contributing to the formation of photochemical smog. Silwipe 25 is low in odor and particularly effective at removing silicone oil and grease contaminants.

### Benefits

- Evaporate quickly
- Low toxicity
- No ozone depleting substances
- No halogenated solvents
- Leaves absolutely no residue
- Safe on all metals and other critical surfaces\*
- Broad range of material compatibility

### Applications

Silwipe 25 quickly and easily removes dirt, dust, light oils, grease, and other deposits from metallic and non-metallic surfaces. Simply spray and wipe to flush off soils and surface will air dry in seconds.

\* We suggest that you always test critical surface compatibility or call us for tech support.

### Key Physical Characteristics

| <u>Property</u>             | <u>Silwipe 25</u>            |
|-----------------------------|------------------------------|
| Boiling Point               | 100 °C                       |
| Appearance                  | Clear, Colorless Liquid      |
| Evaporation Rate (nBuAc=1)  | > 1.0                        |
| Flash Point, Tag Closed Cup | -1° C                        |
| Odor                        | Mild                         |
| Solubility in Water         | Negligible                   |
| Specific Gravity (H2O=1)    | 0.815                        |
| Vapor Density (Air=1)       | >1                           |
| Vapor Pressure (mm Hg):     | ~1.3 @ 20°C                  |
| VOC Content – Except CA     | Exempt compound (0 gm/liter) |
| VOC Content – California    | 25 gm/liter                  |

### Safety and Handling Precautions

Silwipe 25 is a flammable liquid that should never be used around open flames, (welding torches, for example). Always use with adequate ventilation. Rubber gloves are recommended. Place rags in a metal sealable container after use to avoid possible spontaneous combustion. Keep container closed. Avoid excessive contact with fumes or liquid. Treat this chemical with respect and follow all MSDS instructions.

### Packaging

| <u>Product Name</u> | <u>Packaging</u>  |
|---------------------|-------------------|
| Silwipe 25          | 55 Gallon Drums   |
| Silwipe 25          | 5 Gallon Pails    |
| Silwipe 25          | 4 x 1 Gallon Cans |