

ZC-026 HIGH TEMP



Product description:

AVIONIC CORROSION PREVENTIVE

FEATURES:

 A medium to heavy duty water displacing, thin film, corrosion preventive

KEY BENEFITS:

- Does not harm most paints, plastic, or insulation
- Ideal for protecting electrical connectors from corroding
- Thixotropic property of ZC-026 High Temp prevents it from disrupting contact between connectors
- Protects cables and surfaces as well as other interior and exterior aircraft surfaces
- The cured film of ZC-026 High Temp can withstand temperatures as low as -55°C (-67°F) and as high as 115°C (239°F) continuously



- Provides superior protection to avionic connectors and components and has lubricating properties to prevent fretting corrosion
- Penetrates mated connectors to provide corrosion protection for assembly and in-service components
- ► The coating can withstand temperatures up to 150°C (302°F) for 500 hours cumulative
- Prevents corrosion including corrosion in the harshest environments

Rev: 29338A 10-20-2021







Product description:

AVIONIC CORROSION PREVENTIVE

KEY BENEFITS:

ZC-026 High Temp works well in processes where higher process temperatures are required to reduce whiskering in low or no-tin plate metals

APPLICATIONS:

- ✓ Use **ZC-026 High Temp** on highly critical metal surfaces and avionic components where high temperature exposure may be an issue.
- ✓ For removal of ZC-026 High Temp, use ZC-640 (D-5640NS), Sur-Prep® 3160, or Sur-Prep® 3167.

PHYSICAL PROPERTIES:

- ► Specific Gravity (H₂O=1): 0.86
- Vapor Density: Heavier than air
- Evaporation Rate: Slower than ether

AVAILABLE PACK SIZES:

▶ 5 Gallon (18.9L) Pails-010830]



