



DW410

Thermal Spray Tape

DeWAL® DW410 is a blue silicone rubber-coated glass fabric with a high temperature silicone adhesive. The silicone rubber is tough, abrasion resistant, and able to withstand high temperatures as well as grit blasting impact. The silicone adhesive provides excellent adhesion at high temperatures yet removes cleanly.

Applications:

- Masking tape in grit blasting, plasma, and flame spraying

Industry(s):

- Aerospace
- Plasma & Thermal Spray Masking

Features and Benefits

- Removes cleanly at elevated temperatures
- Excellent abrasion resistance
- One-step plasma masking tape
- Prevents bridging during metallization process

| Basic Physical Properties | Typical Value                 | Units           | Test Method |
|---------------------------|-------------------------------|-----------------|-------------|
| Adhesion to Steel         | 469 / 42                      | g/cm / oz/in    | ASTM-D 1000 |
| Color                     | Blue                          | N/A             | N/A         |
| Construction              | Typical Value                 | Units           | Test Method |
| Substrate                 | Silicone Rubber & Glass Cloth | N/A             | N/A         |
| Substrate Thickness       | 0.203 / 0.008                 | mm / in         | N/A         |
| Adhesive System           | Silicone                      | N/A             | N/A         |
| Adhesive Thickness        | 0.0765 / 0.003                | mm / in         | N/A         |
| Overall Thickness         | 0.2794 / 0.011                | mm / in         | ASTM-D374   |
| Min Width                 | 6.35 / 0.25                   | mm / in         | N/A         |
| Max Width                 | 914 / 36                      | mm / in         | N/A         |
| Heat and Flame            | Typical Value                 | Units           | Test Method |
| Max Operating Temp.       | 260 / 500                     | °C / °F         | N/A         |
| Processing & Packaging    | Typical Value                 | Units           | Test Method |
| Shelf Life                | 18                            | Months from DOM | N/A         |
| Shelf Life Storage Temp.  | 21 / 70                       | °C / °F         | N/A         |
| Roll Length               | 33 / 36                       | m / yd          | N/A         |
| Standard Core Type        | DeWAL Paper                   | N/A             | N/A         |
| Core Diameter             | 76 / 3                        | mm / in         | N/A         |
| Standard Liner            | Yellow Bubble                 | N/A             | N/A         |

Specifications  
Specification(s) GE: C10 - 12, PMC 4416, RR: OMAT 2/174C

- Typical values shown are from testing at date of manufacture and should not be used for specification limits.
- Additional technical information and product specifications are available upon request.
- Shelf life is 18 months from the date of manufacture with storage conditions of 21°C (70°F) and 50% RH.
- All metric conversions are approximate.

Note: Shelf life is defined as the duration of time for which the product will meet the physical characteristics outlined on this page. It does not guarantee the product's usefulness in all applications.

The information contained in this Data Sheet is intended to assist you in designing with Rogers' Elastomeric Material Solutions. It is not intended to and does not create any warranties, express or implied, including any warranty of merchantability or fitness for a particular purpose or that the results shown in this Data Sheet will be achieved by a user for a particular purpose. The user should determine the suitability of Rogers DeWAL products for each application. The Rogers logo, DeWAL logo and DeWAL are trademarks of Rogers Corporation or one of its subsidiaries.

