

ACL INC -- 6001, MAT & TABLETOP CLEANER -- 6850-01-283-9966

=====
===== Product Identification =====

Product ID:6001, MAT & TABLETOP CLEANER

MSDS Date:04/02/2001

FSC:6850

NIIN:01-283-9966

Status Code:A

MSDS Number: CLRDS

=== Responsible Party ===

Company Name:ACL INC

Address:1960 E DEVON AVE

City:ELK GROVE VILLAGE

State:IL

ZIP:60007

Country:US

Info Phone Num:847-981-9212

Emergency Phone Num:800-535-5053

CAGE:65565

=== Contractor Identification ===

Company Name:ACL INC

Address:1960 E DEVON AVE

Box:City:ELK GROVE VILLAGE

State:IL

ZIP:60007

Country:US

Phone:847-981-9212

CAGE:65565

=====
===== Composition/Information on Ingredients =====

Ingred Name:DIETHANOL AMIDE OF COCONUT FATTY ACID

CAS:111-42-2

RTECS #:KL2975000

< Wt:1.

ACGIH TLV:2 MG/M3;0.46 PPM

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:SODIUM TRIPHOSPHATE

CAS:7758-29-4

RTECS #:YK4570000

< Wt:1.

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:SODIUM HYDROXIDE

CAS:1310-73-2

RTECS #:WB4900000

< Wt:1.

OSHA PEL:2 MG/M3

ACGIH STEL:C2 MG/M3

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:DEIONIZED WATER

CAS:7732-18-5
RTECS #:ZC0110000
Minumum % Wt:95.
Maxumum % Wt:99.

Ingred Name:TETRASODIUM ETHYLENEDIAMINETETRAACETATE
CAS:64-02-8
RTECS #:AH5075000
< Wt:1.

Ingred Name:ISOPROPANOL
CAS:67-63-0
RTECS #:NT8050000
= Wt:.4
OSHA PEL:980 MG/M3;400 PPM
ACGIH TLV:983 MG/M3;400 PPM
ACGIH STEL:1230 MG/M3;500 PPM

Ingred Name:DODECYLBENZENESULFONIC ACID
CAS:27176-87-0
RTECS #:DB6600000
< Wt:1.
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:POLY(OXY-1,2-ETHANEDIYL)
CAS:9016-45-9
RTECS #:AX0247000
< Wt:1.

=====
===== Hazards Identification =====

Health Hazards Acute and Chronic:INHALATION: NO OBSERVABLE EFFECTS OF
OVEREXPOSURE. EYES: MILD IRRITATION. SKIN: VERY MILD, IF ANY,
IRRITATION. INGESTION: NAUSEA AND DIARRHEA ARE POSSIBLE.

=====
===== First Aid Measures =====

First Aid:INHALATION-MOVE TO FRESH AIR IN CASE OF ACCIDENTIAL OVER
INHALATION OF VAPORS. IF BREATHING HAS STOPPED, GIVE ARTIFICIAL
RESPIRATION. CALL FOR PROMPT MEDICAL AID. EYE-FLUSH EYES WITH LARGE
AMOUNTS OF WATER FOR 15 MINS OR UNTIL IRRITATION SUBSIDE. IF
IRRITATION PERSISTS, GET MEDICAL AID. SKIN-REMOVE CONTAMINATED
CLOTHING (INCLUDING SHOES) & WASH BEFORE REUSE. RINSE AREA WITH
WATER. IF IRRITATION P ERSISTS, SEEK MEDICAL AID. INGESTION-DO NOT
INDUCE VOMITING UNLESS DIRECTED BY A PHYSICIAN. IF CONSCIOUS &
ALERT GIVE 2 GLASSES OF WATER. SEEK MEDICAL AID IMMEDIATELY.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:NONE
Extinguishing Media:WATER, FOAM, DRY CHEMICAL, CARBON DIOXIDE.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD WEAR SELF CONTAINED
POSITIVE-PRESSURE BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:HAZARDOUS COMBUSTION PRODUCTS: SMOKE,
FUMES AND OXIDES OF CARBON.

===== Accidental Release Measures =====

Spill Release Procedures:LAND SPILL: PICK UP AND PLACE IN APPROPRIATE CONTAINER. WATER SPILL: NA

===== Handling and Storage =====

Handling and Storage Precautions:STORAGE TEMPERATURES: AMBIENT. STORAGE PRESSURE: ATMOSPHERIC.

Other Precautions:GENERAL: KEEP CONTAINER CLOSED WHEN NOT IN USE. STORE IN COOL, WELL VENTILATED PLACE OUT OF DIRECT SUNLIGHT AND AWAY FROM INCOMPATIBLE MATERIALS. (SEE STABILITY AND REACTIVITY SECTION). FOLLOW ALL MATERIAL SAFETY DATA SHEET AND LABEL WARNINGS EVEN AFTER CONTAINER IS EMPTIED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:RESPIRATOR: IF CONCENTRATIONS ARE OVER THE EXPOSURE LIMIT AND ARE KNOWN, AIR PURIFYING RESPIRATOR WITH ORGANIC VAPOR CARTRIDGES MAY BE ACCEPTABLE. REFER TO CARTRIDGES FOR ACCEPTABLE LEVELS. IF CONCENTRATIONS ARE OVER EXPOSURE LIMIT AND ARE UNKNOWN, USE A SUPPLIED AIR RESPIRATOR.

Ventilation:LOCAL EXHAUST VENTILATION ACCEPTABLE.

Protective Gloves:RECOMMENDED: SOLVEX, BUTYL, NATURAL LATEX, NEOPRENE, BUNA.

Eye Protection:SAFETY GLASSES.

Supplemental Safety and Health

PRODUCT NAME: MAT & TABLETOP CLEANER. PRODUCT NUMBER: #6001, #6001S, #6002.

===== Physical/Chemical Properties =====

HCC:B3

Boiling Pt:=100.C, 212.F

Melt/Freeze Pt:=0.C, 32.F

Vapor Density:(AIR=1) NE

VOC Pounds/Gallon:1

pH:7.2

Viscosity:NA

Evaporation Rate & Reference:NE (H2O=1)

Solubility in Water:100

Appearance and Odor:CLEAR BLUE LIQUID; ODOR: PLEASANT

Percent Volatiles by Volume:>70

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE

Stability Condition to Avoid:NONE

Hazardous Decomposition Products:SMOKE, FUMES AND OXIDES OF CARBON.

===== Toxicological Information =====

Toxicological Information:RESULTS OF COMPONENT TOXICITY TEST PERFORMED: INFORMATION NOT AVAILABLE. HUMAN EXPERIENCE: INFORMATION NOT AVAILABLE.

=====
Ecological Information
=====

Ecological:FURTHER INFORMATION: INFORMATION NOT AVAILABLE.

=====
Disposal Considerations
=====

Waste Disposal Methods:FEDERAL, STATE, AND LOCAL LAWS GOVERNING
DISPOSAL OF MATERIAL CAN DIFFER. ENSURE PROPER DISPOSAL COMPLIANCE
WITH PROPER AUTHORITIES BEFORE DISPOSAL.

=====
MSDS Transport Information
=====

Transport Information:U.S. DOT INFORMATION. BASIC DESCRIPTION: NON
HAZARDOUS MATERIAL. PROPER SHIPPING NAME: NA. HAZARD CLASS: NA.
PACKAGING GROUP: NA. UN NUMBER: NA. LIMITATIONS: NA. IATA. PROPER
SHIPPING NAME: NON HAZARD OUS MATERIAL. HAZARD CLASS: NA. PACKING
GROUP: NA. UN NUMBER: NA. LIMITATIONS: NA.

=====
Regulatory Information
=====

SARA Title III Information:CERCLA/SUPERFUND, 40 CFR 117, 302: NONE OF
THE CHEMICALS ARE SECTION 302 HAZARDS. SARA SUPERFUND &
REAUTHORIZATION ACT OF 1986 TITLE III SECTIONS 302, 311,312 & 313:
SECTION 302 ? EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355): NONE OF
THE CHEMICALS ARE SECTION 302 HAZARDS. SECTION 311/312 ? MATERIAL
SAFETY DATA SHEET REQUIREMENTS (40 CFR 370): (X) BY OUR HAZARD
EVALUATION, THIS PRODUCT IS NON-HAZAR DOUS. SECTION 313 ? LIST OF
TOXIC CHEMICALS (40CFC 372):THIS PRODUCT CONTAINS THE FOLLOWING
CHEMICALS (AT LEVEL OF 1% OR GREATER)WHICH ARE FOUND ON THE 313
LIST OF TOXIC CHEMICALS: NONE OF THE CHEMIC ALS ARE SECTION 313
HAZARDS.

Federal Regulatory Information:OSHA HAZARDOUS COMPONENTS (29 CFR
1910.1200): EXPOSURE LIMITS 8. HOURS TWA (PPM):
ISOPROPANOL=400-ACGIH TLV. MSDS COMPLIES WITH OSHAS HAZARD
COMMUNICATION RULE, 29 CFR 1910.1200. TOXIC SUBSTANCE CONTR OL ACT
(TSCA): ALL SUBSTANCES ARE TSCA LISTED. FEDERAL WATER POLLUTION
CONTROL ACT, CLEAN WATER ACT, 40 CFR 401.15-(FORMERLY SECTION 307),
40 CFR 116 (FOMERLY SECTION 311) THIS PRODUCT CONTAINS THE FO
LLOWING CHEMICALS WHICH ARE LISTED: NONE. CLEAN AIR ACT: NO
INFORMATION.

State Regulatory Information:CALIFORNIA PROPOSITION 65: THIS PRODUCT
CONTAINS THE FOLLOWING INGREDIENTS WHICH APPEAR ON THE CALIFORNIA
PROPOSITION 65 LIST: CHEMICAL, C.A.S. NUMBER, WEIGHT%: NONE OF THE
CHEMICALS ARE ON THE PROPOS ITION 65 LIST.

=====
Other Information
=====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.