

Revision Number: 008.0 Issue date: 11/10/2014

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: BONDERITE C-IC 33 AERO ACID IDH number: 594015

DEOXIDIZER known as TURCO

ALUMIPREP 33

Product type: Acidic Cleaner for Industrial Application

Company address:

Henkel Corporation

One Henkel Way Rocky Hill, Connecticut 06067

Restriction of Use: None identified

United States Region:

Contact information:

Telephone: (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: COMBUSTIBLE LIQUID.

MAY BE CORROSIVE TO METALS.

HARMFUL IF SWALLOWED OR IN CONTACT WITH SKIN. CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.

MAY CAUSE AN ALLERGIC SKIN REACTION.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	4
CORROSIVE TO METALS	1
ACUTE TOXICITY ORAL	4
ACUTE TOXICITY DERMAL	4
SKIN CORROSION	1B
SERIOUS EYE DAMAGE	1
SKIN SENSITIZATION	1



Precautionary Statements

Keep away from heat, sparks, open flames, hot surfaces - no smoking. Keep only in original Prevention:

container. Do not breathe vapors, mist, or spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out

of the workplace. Wear protective gloves, eye protection, and face protection.

If SWALLOWED: Immediately call poison control or physician if you feel unwell. IF Response:

SWALLOWED: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove person to fresh air and keep comfortable for

breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. Immediately call a poison control center or physician. If skin irritation or rash occurs: Get medical attention. Wash contaminated clothing before reuse. In case of fire: Use foam, dry chemical or carbon dioxide to extinguish. Absorb spillage to prevent material damage.

Storage: Store in a well-ventilated place. Keep cool. Store locked up. Store in corrosive resistant

container with a resistant inner liner.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Phosphoric acid	7664-38-2	10 - 30
2-Butoxyethanol	111-76-2	10 - 30
Potassium phosphate	Proprietary	1 - 5
Hydrogen fluoride	7664-39-3	0.1 - 1

^{*} Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: If mist or vapor of this product is inhaled, remove person immediately to fresh

air. Seek medical attention if symptoms develop or persist.

Skin contact: Remove contaminated clothing and footwear. For skin contact, flush with large

amounts of water. Seek immediate medical attention.

Eye contact: In case of contact with the eyes, rinse immediately with plenty of water for 15

minutes, and seek immediate medical attention.

Ingestion: Get immediate medical attention. Do not induce vomiting. Give one to two

glasses of water or milk. Never give anything by mouth to a victim who is

unconscious or is having convulsions.

Symptoms: See Section 11.

IDH number: 594015

Notes to physician: Treatment of hypocalcemia associated with corrosive fluoride compounds

exposure may be corrected by intravenous calcium gluconate or calcium chloride. Treatment of hypomagnesemia may be corrected by intravenous

magnesium sulfate.

5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide. Use media

appropriate for surrounding material.

Special firefighting procedures: Wear full protective clothing. Wear self-contained breathing apparatus.

Unusual fire or explosion hazards: Fire and explosion hazards are moderate when this product is exposed to heat

or flame. Vapors are heavier than air and may travel along floor to an ignition

source.

Hazardous combustion products: Irritating and toxic gases or fumes may be released during a fire.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Prevent further leakage or spillage if safe to do so. Wear appropriate

protective equipment and clothing during clean-up.

Clean-up methods: Absorb spill with inert material. Shovel material into appropriate container for

disposal.

7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Do

not inhale vapors and fumes. Keep away from heat, spark and flame. For

industrial use only.

Storage: For safe storage, store between 40 °F (4.4 °C) and 100 °F (37.8 °C)

Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Do not pressurize, cut, heat or weld containers. Empty product containers may contain product residue. Do not reuse empty

containers. Thaw and mix thoroughly if frozen.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Phosphoric acid	3 mg/m3 STEL 1 mg/m3 TWA	1 mg/m3 PEL	None	None
2-Butoxyethanol	20 ppm TWA	50 ppm (240 mg/m3) PEL (SKIN)	None	None
Potassium phosphate	None	None	None	None
Hydrogen fluoride	2 ppm Ceiling (as F) 0.5 ppm TWA (as F) (SKIN) (as F)	2.5 mg/m3 PEL (as F) 3 ppm TWA	None	None

Engineering controls: Use general ventilation and use local exhaust, where possible, in confined or

enclosed spaces.

Respiratory protection: If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or

vapors, appropriate NIOSH/MSHA respiratory protection must be provided.

Eye/face protection: Wear chemical goggles; face shield (if splashing is possible).

Skin protection: Wear impervious gloves for prolonged contact. Use of impervious apron and

boots are recommended. Gloves should be tested to determine suitability for

prolonged contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:

Color:
Color:
Odor:
Odor threshold:
pH:
Vapor pressure:

Liquid
Colorless
Solvent
Not available.

2
Vapor pressure:
Not determined

Boiling point/range: > 200 °F (> 93.3 °C) Melting point/ range: 15 °F (-9.4 °C)

Specific gravity: Vapor density: 1.12 - 1.16 at 15.6 °C (60.08 °F)

Not determined

Flash point: 62.8 °C (145.04 °F) Tagliabue closed cup

Flammable/Explosive limits - lower: Not available. Flammable/Explosive limits - upper: Not available. Autoignition temperature: Not applicable Evaporation rate: Not available. Solubility in water: Complete Partition coefficient (n-octanol/water): Not determined

VOC content: 14 % (by weight) (estimated)

Viscosity: Not available. **Decomposition temperature:** Not available.

10. STABILITY AND REACTIVITY

Stability: Stable at normal conditions.

Hazardous reactions: Will not occur.

Hazardous decomposition Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low products:

molecular weight hydrocarbons. May liberate hydrogen fluoride.

Incompatible materials: This product may react with strong oxidizing agents.

Reactivity: Not available.

IDH number: 594015

Conditions to avoid: Keep away from heat, ignition sources and incompatible materials.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects/Symptoms

Inhalation: Mists, vapors or liquid may cause severe irritation or burns. Inhalation of mists or vapors may

produce upper airway edema, wheezing, pulmonary edema, pneumonitis and respiratory

Skin contact: Corrosive to the skin. Contact with the skin or mucous membranes may cause severe irritation

and burns. Following skin exposure to this product, the sensation of irritation or pain may be delayed. A component in this product may be harmful or fatal if absorbed through the skin.

Eye contact: This product is severely irritating to the eyes and may cause irreversible damage including

burns and blindness.

Ingestion: This product may produce corrosive damage to the gastrointestinal tract if it is swallowed. May

cause dizziness, incoordination, headache, nausea, and vomiting. Product contains a glycol

ether which caused blood disorders in rabbits.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects	
Phosphoric acid	Oral LD50 (RAT) = 1,530 mg/kg Dermal LD50 (RABBIT) = 2,740 mg/kg	Irritant, Corrosive	
2-Butoxyethanol	Oral LD50 (RAT) = 560 mg/kg Oral LD50 (RABBIT) = 0.32 g/kg Oral LD50 (RAT) = 1.48 g/kg Dermal LD50 (RABBIT) = 400 mg/kg Inhalation LC50 (RAT, 4 h) = 486 ppm Inhalation LC50 (RAT, 4 h) = 450 ppm	Blood, Central nervous system, Irritant, Kidney, Liver	
Potassium phosphate	None	Gastrointestinal, Irritant, Metabolic	
Hydrogen fluoride	Inhalation LC50 (RAT, 15 min) = 2689 ppm Inhalation LC50 (RAT, 1 h) = 1278 ppm Inhalation LC50 (RAT, 30 min) = 2042 ppm Inhalation LC50 (RAT, 5 min) = 4970 ppm	Allergen, Blood, Bone Marrow, Cardiac, Central nervous system, Corrosive, Irritant, Kidney, Liver, Lung, Muscle, Nervous System, Respiratory, Teeth	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Phosphoric acid	No	No	No
2-Butoxyethanol	No	No	No
Potassium phosphate	No	No	No
Hydrogen fluoride	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

IDH number: 594015

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal. This

product contains a alkylphenol or nonylphenol ethoxylate.

Hazardous waste number: This product, if discarded directly, would be a characteristic RCRA corrosive

waste (D002). This product contains a component or components identified as

hazardous under 40 CFR 261.24. U134: Hydrogen fluoride

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Corrosive liquid, acidic, inorganic, n.o.s. (Phosphoric acid, Hydrofluoric acid)

Hazard class or division: 8
Identification number: UN 3264

Packing group:

DOT Hazardous Substance(s): Hydrofluoric acid, Phosphoric acid

International Air Transportation (ICAO/IATA)

Proper shipping name: Corrosive liquid, acidic, inorganic, n.o.s. (Phosphoric acid, Hydrofluoric acid)

Hazard class or division: 8
Identification number: UN 3264

Packing group:

Water Transportation (IMO/IMDG)

Proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Phosphoric acid,

Hydrofluoric acid)

Hazard class or division: 8 UN 3264

Packing group:

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis CERCLA/SARA Section 311/312: Immediate Health, Delayed Health, Fire

CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of

section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40

CFR 372). 2-Butoxyethanol (CAS# 111-76-2).

CERCLA Reportable quantity: Phosphoric acid (CAS# 7664-38-2) 5,000 lbs. (2,270 kg)

Hydrogen fluoride (CAS# 7664-39-3) 100 lbs. (45.4 kg)

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

Canada Regulatory Information

IDH number: 594015

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

Product name: BONDERITE C-IC 33 AERO ACID DEOXIDIZER known as TURCO ALUMIPREP 33

Page 6 of 7

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: John DiCerbo, Sr. Regulatory Affairs Specialist

Issue date: 11/10/2014

IDH number: 594015

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.