

SPECIALTY GRADE 14-DAY UV RESISTANT OUTDOOR CLOTH DUCT TAPE

TYPICAL APPLICATIONS

- Designed specifically for two and three-step (Scratch, Brown and Finish) stucco applications where the job requirements dictate that the protective barrier be left in place for the entire application

ADVANTAGES AND BENEFITS

- UV inhibitors in both the film and adhesive eliminate residue, reducing clean-up time and expense
- Straight tear along the width and length ensures superior protection in corners and around irregular surfaces, preventing water penetration, lifting, splintering and curling
- Aggressive adhesive holds strong to dusty surfaces and resists lifting during multiple cleaning cycles
- White, waterproof backing significantly reduces heat absorption

CONSTRUCTION

Overall Grade/Function: Specialty/Extended Outdoor
Backing: UV resistant polyethylene film
Adhesive: Synthetic/natural rubber blend

COLOR(S)



Red (RED)



White (WHI)



STANDARD WIDTH(S)

48 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

| | STANDARD | METRIC |
|-----------------------------|-------------------|--------------|
| Tensile Strength | 27.5 lbs/in width | 48.1 N/10 mm |
| Adhesion to Stainless Steel | 70 oz/in width | 7.66 N/10 mm |
| Thickness | 11 mils | 0.28 mm |
| Elongation | 15% | 15% |
| Maximum Temperature | 200 F | 93 C |

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

*Shurtape® is a registered trademark of Shurtape Technologies, LLC

Form# TDS-PC-668-10/02/2013