

# LETAPE

## Adhesive tape

Ideally suited to tool maintenance applications

### Features

- High modulus PTFE tape.
- Excellent release and temperature resistance.
- Application is very simple, due to the tape having no backing liner, and it strips easily after use.
- Ideal for many applications including temporary tool surface repairs, sealing of split moulds to prevent resin preparation, and where localised tool release in tight angles is required.

### Properties

Maximum cure temperature	180°C 232°C	356°F 450°F
Colour	Brown	
Adhesive	Acrylic and Silicone	
Carrier	PTFE	
Total thickness	89µm	0.0035in
Adhesive thickness	38µm	0.0015in
Tape thickness	51µm	0.002in
Elongation at break	150%	

### Availability

Standard width	Up to 100mm	Up to 3.9in
Standard length	33m	36yd

### Storage

No special storage conditions.

### Health & safety

Handling of these products must conform to individual company guidelines and health and safety regulations.

All statements, technical information and recommendations contained in this data sheet are given in good faith and are based on tests believed to be reliable, but their accuracy and completeness are not guaranteed. They do not constitute an offer to any person and shall not be deemed to form the basis of any subsequent contract. All products are sold subject to the Cytec's Standard Terms and conditions of Sale. Accordingly, the user shall determine the suitability of the products for their intended use prior to purchase and shall assume all risk and liability in connection therewith. It is the responsibility of those wishing to sell items made from or embodying the products to inform the user of the properties of the products and the purposes for which they may be suitable, together with all precautionary measures required in handling those products. The information contained herein is under constant review and liable to be modified from time to time.

© Copyright 2012 – Cytec Process Materials (Keighley) Ltd, Cytec Process Materials (CA) Inc, Cytec Process Materials (Toulouse) Sarl, Cytec Process Materials (Milan) Srl. All rights reserved worldwide. All trademarks or registered trademarks are the property of their respective owners.