

FEROCIOUSLY STRONG MONSTER OF ALL DUCT TAPES

TYPICAL APPLICATIONS

- Rough surfaces
- Heavy repairs
- Bottom board tape in manufactured housing

ADVANTAGES AND BENEFITS

- Extra thick adhesive for quick stick on rough surfaces
- Superior holding power
- Waterproof backing provides durable protection

CONSTRUCTION

Overall Grade/Function: Heavy Duty
Backing: Waterproof polyethylene film with a cloth carrier
Adhesive: Natural rubber

COLOR(S)

 Metallic Silver (MSL)

STANDARD WIDTH(S) STANDARD LENGTH(S)

48 mm 40 yd

Contact your Shurtape sales representative for other available sizes.



PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	52 lbs/in width	91.0 N/10 mm
Adhesion to Stainless Steel	90 oz/in width	9.85 N/10 mm
Thickness	17 mils	0.43 mm
Elongation	10%	10%
Service Temperature Range	50 F to 200 F	10 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

*Shurtape[®] is a registered trademark of Shurtape Technologies, LLC

Form# TDS-PC-754-TREX-10/11/2013