

**DBT 04J
Tin Catalyst (DBT)****1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

Manufactured By: Momentive performance material
260 Hudson River Rd
Waterford NY 12188

Revised: 04/21/2011

Preparer: PRODUCT STEWARDSHIP COMPLIANCE AND STANDARDS
CHEMTREC 1-800-424-9300

Chemical Family/Use: Catalyst
Formula: Catalyst

HMIS
Flammability: 1 Reactivity: 0 Health: 2

NFPA
Flammability: 1 Reactivity: 0 Health: 2

2. HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW**

WARNING! Causes skin and eye irritation. May cause irritation to the respiratory system. Harmful: danger of serious damage to health by prolonged exposure if swallowed. May cause adverse reproductive effects.

Form: Liquid **Color:** Colorless **Odor:** Faint

POTENTIAL HEALTH EFFECTS**INGESTION**

Affects: - mouth, throat, esophagus and stomach Causes the following effects: - discomfort or pain in the mouth, throat, chest and abdomen

SKIN

Causes the following effects: - discomfort or pain - swelling

INHALATION

Vapors given off by heated product may be harmful. May cause irritation to the respiratory system.

EYES

Causes the following effects: - discomfort or pain - excess blinking - tear production - marked excess redness of the conjunctivae - swelling of the conjunctivae

MEDICAL CONDITIONS AGGRAVATED

Central nervous system disorders.

SUBCHRONIC (TARGET ORGAN)

Central nervous system.

DBT 04J
Tin Catalyst (DBT)**CHRONIC EFFECTS / CARCINOGENICITY**

This product or one of its ingredients present at 0.1% or more is NOT listed as a carcinogen or suspected carcinogen by NTP, IARC, or OSHA.

ROUTES OF EXPOSURE

Dermal; Oral; Eye

3. COMPOSITION/INFORMATION ON INGREDIENTS**PRODUCT COMPOSITION****CAS REG NO.****WGT. %****A. HAZARDOUS**

Dibutyltin Dilaurate

77-58-7

60 - 100 %

B. NON-HAZARDOUS**4. FIRST AID MEASURES****INGESTION**

Do not induce vomiting. Slowly dilute with 1-2 glasses of water and seek medical attention. Never give anything by mouth to an unconscious person.

SKIN

Wash area with soap and water. Wash contaminated clothing before reuse. Get medical attention if symptoms occur.

INHALATION

Move to fresh air. Get medical attention if symptoms persist.

NOTE TO PHYSICIAN

Treatment is symptomatic and supportive.

5. FIRE-FIGHTING MEASURES

FLASH POINT:

ca. 235 °C; 455 °F

IGNITION TEMPERATURE:

> 300 °C; 572 °F

FLAMMABLE LIMITS IN AIR - LOWER (%):

3.30 %(V).

**DBT 04J
Tin Catalyst (DBT)**

FLAMMABLE LIMITS IN AIR - UPPER (%): 19.00 %(V).**SENSITIVITY TO MECHANICAL IMPACT:** No**SENSITIVITY TO STATIC DISCHARGE**

Sensitivity to static discharge is not expected., Do not taste or swallow., Wash thoroughly after handling.

EXTINGUISHING MEDIA

All standard extinguishing agents are suitable.

SPECIAL FIRE FIGHTING PROCEDURES

Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES**ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED**

Wipe, scrape or soak up in an inert material and put in a container for disposal. Warn other workers of spill. Wash walking surfaces with detergent and water to reduce slipping hazard. Wear proper protective equipment as specified in the protective equipment section. Avoid runoff to natural waters a component is known to be toxic to marine life.

7. HANDLING AND STORAGE**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE**

Use only in well-ventilated areas. Avoid contact with skin and eyes. Avoid inhalation of vapors and spray mists. Keep container closed. Wash hands before eating, drinking, or smoking. Keep out of reach of children.

STORAGE

Store in tightly closed original container in a dry and cool place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**ENGINEERING CONTROLS**Eye wash facilities and emergency shower must be available when handling this product.; Showers;
Exhaust ventilation**RESPIRATORY PROTECTION**

None known.

DBT 04J
Tin Catalyst (DBT)**PROTECTIVE GLOVES**

Impermeable or chemical resistant gloves.

OTHER PROTECTIVE EQUIPMENT

None known.

Exposure Guidelines

Component	CAS RN	Source	Value
Dibutyltin Dilaurate	77-58-7	ACGIH, TWA	0.1 mg/m3
Dibutyltin Dilaurate	77-58-7	ACGIH, STEL	0.2 mg/m3
Dibutyltin Dilaurate	77-58-7	ACGIH, SKIN_DES	Can be absorbed through the skin.
Dibutyltin Dilaurate	77-58-7	OSHA Z1, PEL	0.1 mg/m3
Dibutyltin Dilaurate	77-58-7	ACGIH, TWA	2 mg/m3
Dibutyltin Dilaurate	77-58-7	OSHA Z1, PEL	2 mg/m3

Absence of values indicates none found

PEL - OSHA Permissible Exposure Limit; TLV - ACGIH Threshold Limit Value; TWA - Time Weighted Average; INTL REL - Internal Recommended Exposure Limit

OSHA revoked the Final Rule Limits of January 19, 1989 in response to the 11th Circuit Court of Appeals decision (AFL-CIO v. OSHA) effective June 30, 1993. See 29 CFR 1910.1000 (58 FR 35338).

9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT - C & F:	204 °C; 399 °F
VAPOR PRESSURE (20 C) (MM HG):	Negligible
VAPOR DENSITY (AIR=1):	No data available.
FREEZING POINT:	Not applicable
PHYSICAL STATE:	Liquid
Odor:	Faint
Color:	Colorless
EVAPORATION RATE (BUTYL ACETATE=1):	No data available.
SPECIFIC GRAVITY (WATER=1):	1.28
DENSITY:	ca. 1.280 g/cm3
ACID / ALKALINITY (MEQ/G):	No data available.
pH:	Not applicable
SOLUBILITY IN WATER (20 C):	Slightly soluble in water
SOLUBILITY IN ORGANIC SOLVENT (STATE SOLVENT):	No data available.
VOC EXCL. H2O & EXEMPTS (G/L):	27 g/l

**DBT 04J
Tin Catalyst (DBT)**

10. STABILITY AND REACTIVITY**STABILITY**

Stable

HAZARDOUS POLYMERIZATION

Hazardous polymerisation does not occur.

HAZARDOUS THERMAL DECOMPOSITION / COMBUSTION PRODUCTS

Carbon dioxide; Formaldehyde.; Silicon dioxide.; Tin fumes.

INCOMPATIBILITY (MATERIALS TO AVOID)

None known.

CONDITIONS TO AVOID

None known.

11. TOXICOLOGICAL INFORMATION**ACUTE ORAL**

Remarks: Not applicable

ACUTE DERMAL

Remarks: Not applicable

ACUTE INHALATION

Remarks: Not applicable

OTHER

Contains dibutyl tin dilaurate which may cause birth defects and reproductive effects based on animal data., In animal studies with repeated oral application of dibutyl tin compounds toxic effects were observed on the liver, bile duct, brain and immune system.

SENSITIZATION

No data available.

SKIN IRRITATION

Species: Rabbit; Irritant.

EYE IRRITATION

Species: Rabbit ; Result: Irritating to eyes.

MUTAGENICITY

No data available.

OTHER EFFECTS OF OVEREXPOSURE

None known.

DBT 04J
Tin Catalyst (DBT)

12. ECOLOGICAL INFORMATION**ECOTOXICITY**

No data available.

DISTRIBUTION

No data available.

CHEMICAL FATE

No data available.

13. DISPOSAL CONSIDERATIONS**DISPOSAL METHOD**

Disposal should be made in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

DOT SHIPPING NAME: Environmentally hazardous substances, liquid, n.o.s.(DIBUTYLTIN DILAUATE)
DOT HAZARD CLASS: 9
DOT LABEL (S): 9
UN/NA NUMBER: UN3082
PACKING GROUP: III

IMDG SHIPPING NAME: Environmentally hazardous substances, liquid, n.o.s.(DIBUTYLTIN DILAUATE)
CLASS: 9
IMDG-LABELS: 9
UN NUMBER: UN3082
PACKING GROUP: III
EMS No: F-A; S-F

IATA: Environmentally hazardous substances, liquid, n.o.s.(DIBUTYLTIN DILAUATE)
CLASS: 9
ICAO-LABELS: 9MI
UN NUMBER: UN3082
PACKING GROUP: III

Further Information: This substance/preparation meets the criteria of a Marine Pollutant (see IMDG paragraph 2.9.3.3) but is not identified in the IMDG Code (Marpol list). As such, substance/preparation shall be transported as a marine

**DBT 04J
Tin Catalyst (DBT)**

pollutant in accordance with the IMDG code.

15. REGULATORY INFORMATION**Inventories**

Australia Inventory of Chemical Substances (AICS)	y (positive listing)	
EU list of existing chemical substances	y (positive listing)	
Japan Inventory of Existing & New Chemical Substances (ENCS)	y (positive listing)	
China Inventory of Existing Chemical Substances	y (positive listing)	
Korea Existing Chemicals Inventory (KECI)	y (positive listing)	
Canada DSL Inventory	y (positive listing)	
Canada NDSL Inventory	n (Negative listing)	
Philippines Inventory of Chemicals and Chemical Substances (PICCS)	y (positive listing)	
TSCA list	y (positive listing)	On TSCA Inventory

For inventories that are marked as quantity restricted or special cases, please contact Momentive.

US Regulatory Information**SARA (311,312) HAZARD CLASS**
Acute Health Hazard**SARA (313) CHEMICALS****CALIFORNIA PROPOSITION 65**

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

Canadian Regulatory Information**WHMIS HAZARD CLASS**

D1B - Toxic Material Causing Immediate and Serious Toxic Effects
D2B - Toxic Material Causing Other Toxic Effects

DBT 04J
Tin Catalyst (DBT)**16. OTHER INFORMATION****OTHER**

C = ceiling limit NEGL = negligible
EST = estimated NF = none found
NA = not applicable UNKN = unknown
NE = none established REC = recommended
ND = none determined V = recommended by vendor
SKN = skin TS = trade secret
R = recommended MST = mist
NT = not tested STEL = short term exposure limit
ppm = parts per million ppb = parts per billion

By-product= reaction by-product, TSCA inventory status not required under 40 CFR part 720.30(h-2).
These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

**RTV577 012-PAIL KIT (12.063LBS-5.477 KG)
SILICONE RUBBER COMPOUND**

PIN: 9455-21101

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Manufactured By: Momentive performance material
260 Hudson River Rd
Waterford NY 12188

Revised: 09/28/2010
Preparer: PRODUCT STEWARDSHIP COMPLIANCE AND STANDARDS
CHEMTREC 1-800-424-9300

Chemical Family/Use: Silicone Polymer
Formula: Mixture

HMIS

Flammability: 0 Reactivity: 0 Health: 1

NFPA

Flammability: 0 Reactivity: 0 Health: 1

2. HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW**

CAUTION! Irritating to eyes. Attention: Not for injection into humans. No dangerous reaction known under conditions of normal use.

Form: Paste**Color:** white**Odor:** slight**POTENTIAL HEALTH EFFECTS****INGESTION**

May cause stomach discomfort. Not an anticipated route of exposure.

SKIN

May cause mild skin irritation.

INHALATION

None known.

EYES

May cause mild eye irritation.

MEDICAL CONDITIONS AGGRAVATED

None known.

SUBCHRONIC (TARGET ORGAN)

Respiratory disorder; Liver and kidney damage.

CHRONIC EFFECTS / CARCINOGENICITY

This product or one of its ingredients present at 0.1% or more is NOT listed as a carcinogen or

**RTV577 012-PAIL KIT (12.063LBS-5.477 KG)
SILICONE RUBBER COMPOUND**

suspected carcinogen by NTP, IARC, or OSHA.

ROUTES OF EXPOSURE

Eyes; dermal

3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>PRODUCT COMPOSITION</u>	<u>CAS REG NO.</u>	<u>WGT. %</u>
<u>A. HAZARDOUS</u>		
Silicic acid, ethyl ester	11099-06-2	1 - 5 %
Zinc oxide	1314-13-2	10 - 30 %
<u>B. NON-HAZARDOUS</u>		
Methylphenylsiloxane Copolymer	68951-93-9	30 - 60 %
Limestone	471-34-1	10 - 30 %
Caster oil	8001-78-3	1 - 5 %

4. FIRST AID MEASURES**INGESTION**

Do not induce vomiting. If victim is conscious, give 1-3 glasses of water to drink. Never give anything by mouth to an unconscious person. Get medical attention if irritation persists.

SKIN

Wash with soap and water. Get medical attention if irritation or symptoms from Section 3 develop.

INHALATION

If inhaled, remove to fresh air. If not breathing give artificial respiration using a barrier device. If breathing is difficult give oxygen. Get medical attention.

EYES

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

**RTV577 012-PAIL KIT (12.063LBS-5.477 KG)
SILICONE RUBBER COMPOUND****5. FIRE-FIGHTING MEASURES**

FLASH POINT: > 100 °C; 212 °F
IGNITION TEMPERATURE: Not applicable
FLAMMABLE LIMITS IN AIR - LOWER (%): Not applicable
FLAMMABLE LIMITS IN AIR - UPPER (%): Not applicable

SENSITIVITY TO MECHANICAL IMPACT: No

SENSITIVITY TO STATIC DISCHARGE

Sensitivity to static discharge is not expected.

EXTINGUISHING MEDIA

All standard extinguishing agents are suitable.

SPECIAL FIRE FIGHTING PROCEDURES

Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES**ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED**

Wipe, scrape or soak up in an inert material and put in a container for disposal. Wash walking surfaces with detergent and water to reduce slipping hazard.

7. HANDLING AND STORAGE**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE**

Avoid contact with skin and eyes.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**RESPIRATORY PROTECTION**

If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29CFR 1910.134).

PROTECTIVE GLOVES

Rubber gloves

**RTV577 012-PAIL KIT (12.063LBS-5.477 KG)
SILICONE RUBBER COMPOUND****EYE AND FACE PROTECTION**

Safety glasses with side-shields

OTHER PROTECTIVE EQUIPMENT

Wear suitable protective clothing and eye/face protection.

Exposure Guidelines

Component	CAS RN	Source	Value
Zinc oxide	1314-13-2	OSHA Z1, PEL	Fume. 5 mg/m ³
Zinc oxide	1314-13-2	OSHA Z1, PEL	Respirable fraction. 5 mg/m ³
Zinc oxide	1314-13-2	OSHA Z1, PEL	Total dust. 15 mg/m ³
Zinc oxide	1314-13-2	ACGIH, TWA	Respirable fraction. 2 mg/m ³
Zinc oxide	1314-13-2	ACGIH, STEL	Respirable fraction. 10 mg/m ³

Absence of values indicates none found

PEL - OSHA Permissible Exposure Limit; TLV - ACGIH Threshold Limit Value; TWA - Time Weighted Average; INTL REL - Internal Recommended Exposure Limit

OSHA revoked the Final Rule Limits of January 19, 1989 in response to the 11th Circuit Court of Appeals decision (AFL-CIO v. OSHA) effective June 30, 1993. See 29 CFR 1910.1000 (58 FR 35338).

9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT - C & F:	>168 °C; 334 °F
VAPOR PRESSURE (20 C) (MM HG):	Not applicable
VAPOR DENSITY (AIR=1):	Not applicable
FREEZING POINT:	No data available.
PHYSICAL STATE:	Paste
ODOR:	slight
COLOR:	white
EVAPORATION RATE (BUTYL ACETATE=1):	Unknown
SPECIFIC GRAVITY (WATER=1):	ca. 1.35
DENSITY:	ca. 1.35 g/cm ³
ACID / ALKALINITY (MEQ/G):	No data available.
pH:	Not applicable
SOLUBILITY IN WATER (20 C):	insoluble
SOLUBILITY IN ORGANIC SOLVENT (STATE SOLVENT):	negligible
VOLATILE ORGANIC CONTENT:	No data available.

10. STABILITY AND REACTIVITY**STABILITY**

Stable

**RTV577 012-PAIL KIT (12.063LBS-5.477 KG)
SILICONE RUBBER COMPOUND**

HAZARDOUS POLYMERIZATION

Hazardous polymerisation does not occur.

HAZARDOUS THERMAL DECOMPOSITION / COMBUSTION PRODUCTSCarbon dioxide (CO₂); Carbon monoxide; Silicon dioxide.; May generate formaldehyde at temperatures greater than 150 C (300 F). See Section 10 of MSDS for details.**INCOMPATIBILITY (MATERIALS TO AVOID)**

None known.

CONDITIONS TO AVOID

None known.

11. TOXICOLOGICAL INFORMATION**ACUTE ORAL**

Remarks: Unknown

ACUTE DERMAL

Remarks: Unknown

ACUTE INHALATION

Remarks: No data available.

OTHER

No data available.

SENSITIZATION

No data available.

SKIN IRRITATION

No data available.

EYE IRRITATION

No data available.

MUTAGENICITY

Unknown

12. ECOLOGICAL INFORMATION**ECOTOXICITY**

No data available.

**RTV577 012-PAIL KIT (12.063LBS-5.477 KG)
SILICONE RUBBER COMPOUND****DISTRIBUTION**

No data available.

13. DISPOSAL CONSIDERATIONS**DISPOSAL METHOD**

Disposal should be made in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION**Further Information:**

This product is not regarded as dangerous goods according to the national and international regulations on the transport of dangerous goods.

15. REGULATORY INFORMATION**Inventories**

Australia Inventory of Chemical Substances (AICS)	y (positive listing)	
EU list of existing chemical substances	y (positive listing)	
Japan Inventory of Existing & New Chemical Substances (ENCS)	y (positive listing)	
China Inventory of Existing Chemical Substances	y (positive listing)	
Korea Existing Chemicals Inventory (KECI)	y (positive listing)	
Canada DSL Inventory	y (positive listing)	
Canada NDSL Inventory	n (Negative listing)	
Philippines Inventory of Chemicals and Chemical Substances (PICCS)	y (positive listing)	
TSCA list	y (positive listing)	On TSCA Inventory

For inventories that are marked as quantity restricted or special cases, please contact Momentive.

US Regulatory Information**SARA (311,312) HAZARD CLASS**

Acute Health Hazard; Chronic Health Hazard

SARA (313) CHEMICALS

**RTV577 012-PAIL KIT (12.063LBS-5.477 KG)
SILICONE RUBBER COMPOUND**

CALIFORNIA PROPOSITION 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

Canadian Regulatory Information**WHMIS HAZARD CLASS**

D2B - Toxic Material Causing Other Toxic Effects

Other

SCHDLE B/HTSUS: 3910.00.0000 Silicones in primary forms

ECCN: EAR99

16. OTHER INFORMATION**OTHER**

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate., C = ceiling limit NEGL = negligible EST = estimated NF = none found
NA = not applicable UNKN = unknown NE = none established REC = recommended ND = none determined V = recommended by vendor SKN = skin TS = trade secret R = recommended MST = mist NT = not tested STEL = short term exposure limit ppm = parts per million ppb = parts per billion By-product= reaction by-product, TSCA inventory status not required under 40 CFR part 720.30(h-2).

