

Permatex, Inc.
 10 Columbus Blvd.
 Hartford, CT 06106 USA
 Telephone: 1-87-Permatex
 (877) 376-2839
 Emergency: 800-255-3924 (ChemTel)
 International Emergency: +01-813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: 3H AVIATION FORM-A-GASKET #3 SEALANT .25PT
Item No: 80019
Product Type: Sealant

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH; TLV-TWA	OSHA PEL
VEGETABLE OIL 68187-84-8	30-40	5 mg/m ³	Not listed
ROSIN 8050-09-7	20-30	Not listed	Not listed
TALC 14807-96-6	10-20	2 mg/m ³	20 mppcf
ETHANOL 64-17-5	10-20	1000 ppm	1000 ppm; 1900 mg/m ³
2-PROPANOL 67-63-0	<3	200 ppm	400 ppm; 980 mg/m ³
METHANOL 67-56-1	0.1-1.0	200 ppm	200 ppm; 260 mg/m ³

3. HAZARDS IDENTIFICATION

Toxicity: May cause eye, skin and respiratory irritation.
Primary Routes of Entry: Eye and skin contact, ingestion, inhalation
Signs and Symptoms of Exposure: Excessive accidental exposure may cause headache, dizziness, nausea and mild respiratory irritation.
 Overexposure may cause eye and skin redness.

Component	Weight%	NTP	ACGIH Carcinogens	IARC
TALC 14807-96-6	10-20	male rat-some evidence, female rat-clear evidence, male mice-no evidence, female mice-no evidence	A4- Not classifiable as a human carcinogen	Group 3 Supplement 7, 1987 Monograph 42, 1987
ETHANOL 64-17-5	10-20		A4 - Not Classifiable as a Human Carcinogen	
2-PROPANOL 67-63-0	<3		A4 - Not classifiable as a human carcinogen	Group 3 Monograph 71, 1999; Supp.7, 1987; Monograph 15, 1977

Medical Conditions Recognized as Being Aggravated by Exposure: Preexisting eye, skin and respiratory disorders may be aggravated by overexposure to this product.

4. FIRST AID MEASURES

Ingestion: Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation: Move to fresh air in case of accidental inhalation of vapours. Oxygen or artificial respiration if needed. Obtain medical attention.
Skin Contact: Wash off with soap and water. If skin irritation persists, call a physician.
Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point °F(C°): 60°F TCC

5. FIRE FIGHTING MEASURES

Recommended Extinguishing Media:

Special Fire-Fighting Procedures:

Carbon Dioxide, Dry Chemicals, Foam.

Firefighters should wear self-contained breathing apparatus. Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.

Hazardous Products of Combustion:

Aldehydes, Oxides of carbon, Carboxylic acids

Unusual Fire/Explosion Hazards:

Closed containers may rupture or explode when exposed to extreme heat

Lower Explosive Limit:

2%

Upper Explosive Limit:

12%

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures:

Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal. Residues may be cleaned up with isopropyl alcohol.

7. HANDLING AND STORAGE

Storage:

Store away from heat, sparks or open flame. Do not store at temperatures above 100°F (38°C).

Handling:

Avoid contact with skin and eyes. Do not inhale vapors. Keep container closed when not in use.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes:

Safety glasses.

Skin:

Neoprene or nitrile gloves recommended.

Ventilation:

General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.

Respiratory Protection:

An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Dark brown liquid

Odor:

Alcoholic

Boiling Point:

180°F

pH:

Does not apply

Solubility in Water:

Partial

Specific Gravity:

1.09

VOC(Wt.%):

19.4%

Vapor Pressure:

33 mm Hg @ 68°F

Vapor Density (Air=1):

2.07

Evaporation Rate:

7.7 (ether = 1)

10. STABILITY AND REACTIVITY

Chemical Stability:

Stable at normal conditions

Hazardous Polymerization:

Will not occur

Incompatibilities:

Strong oxidizers

Conditions to Avoid:

Keep away from heat, sparks and open flame. - No smoking.

Hazardous Products of Combustion:

Aldehydes, Oxides of carbon, Carboxylic acids

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations..

US EPA Waste Number: D001 as per 40CFR 261.21

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Ground Transport (DOT)

Product Name: 3H AVIATION FORM-A-GASKET #3
SEALANT .25PT

Item No: 80019

14. TRANSPORTATION INFORMATION

DOT Shipping Name: Consumer Commodity (not more than one liter)
Hazard Class: ORM-D
UN/ID Number: None

IATA

Proper Shipping Name: Consumer Commodity (Not more than 1 liter)
Class or Division: Class 9
UN/ID Number: ID 8000

IMDG

Proper Shipping: Resin Solution, Flammable, Limited Quantity
Hazard Class: Class 3, PG II
UN Number: UN 1866

Marine Pollutant: None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

NONE

California Proposition 65: No California Prop 65 chemicals are known to be present at or above the No Significant Risk Level

TSCA Inventory Status: All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 2, FLAMMABILITY 3, REACTIVITY 0.

Estimated HMIS Classification: HEALTH 2, FLAMMABILITY 3, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety
Company: Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA 06106

Revision Date: October 04, 2010

Revision Number: 3

Telephone No.: 1-87-Permatex (877) 376-2839