

MATERIAL SAFETY DATA SHEET

PR-1826 Adhesion Promoter (RW-3789-44)  
 FM5556

Effective Date: 07/08/03

SECTION I - MANUFACTURER AND PRODUCT INFORMATION

PRC-DeSoto International, Inc.  
 A PPG Industries Company  
 5430 San Fernando Road  
 P.O. Box 1800  
 Glendale, CA 91209

Information Phone: (818) 240-2060  
 Emergency Phone: (800) 228-5635  
 Outside of USA: +(651) 632-9265  
 CHEMTREC: (800) 424-9300

Trade Name: PR-1826 Adhesion Promoter (RW-3789-44)  
 Adhesion promoter  
 Product Code: FM5556  
 Form ID No: X03  
 Product Class: Organosilane solution  
 Synonyms: W-5556

HMIS HAZARD RATING  
 HEALTH - 2  
 FLAMMABILITY - 3  
 REACTIVITY - 0  
 PPE - H  
 None(0)--->Extreme(4)

SECTION II - COMPOSITION

INGREDIENTS INFORMATION

CAS NUMBER	Wt %	CHEMICAL IDENTITY
000078-93-3	60 - 90	Methyl Ethyl Ketone
000067-63-0	10 - 30	Isopropanol
REF00000125	1 - 10	Modified organosilanes
003388-04-3	< 5	Beta-(3,4-Epoxy cyclohexyl) Ethyltrimethoxy Silane
000090-72-2	< 5	Tris-2,4,6-(Dimethylaminomethyl) Phenol
028470-78-2	< 5	Formaldehyde polymer w/ 3-Chloro-1-Propene & Phenol

EXPOSURE LIMITS

CAS NUMBER	EXPOSURE LIMITS (ppm)				S
	ACGIH TLVs		OSHA PELs		
	TWA	STEL	TWA	STEL	
000078-93-3	200	300	200	300	S
000067-63-0	400	500	400	N/E	
REF00000125	N/E	N/E	N/E	N/E	
003388-04-3	N/E	N/E	N/E	N/E	
000090-72-2	5	N/E	10	N/E	R
028470-78-2	N/E	N/E	N/E	N/E	

Footnotes

(S) Occupational Exposure Standard  
 (R) Supplier's Recommended Limit

-----  
MATERIAL SAFETY DATA SHEET

PR-1826 Adhesion Promoter (RW-3789-44)  
FM5556

Effective Date: 07/08/03  
-----

SECTION VI - ACCIDENTAL RELEASE MEASURES  
-----

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Remove all ignition sources. Wear an air-supplied respirator for an unventilated spill. Cover with absorbent. Scoop into containers using non-sparking tools. Clean up residue with a suitable cleaning solvent. Wear appropriate personal protective equipment (See Section VIII).  
-----

SECTION VII - HANDLING AND STORAGE  
-----

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Keep container tightly closed. Isolate from heat, electrical equipment, sparks and flame. Use grounding and bonding procedures during transfer. Do not store above 120 degrees F. Vapors of this product are heavier than air and may collect in low or confined areas. Empty drums may contain explosive vapors. Do not cut, puncture, or weld on or near drum. Wear proper personal protective equipment (See Section VIII). Wash thoroughly after handling and before smoking or eating.  
-----

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION  
-----

ENGINEERING CONTROLS:

Local and/or general ventilation as required to maintain hazardous ingredients below recommended (ACGIH-TLV) or regulated (OSHA-PEL) limits.

RESPIRATORY PROTECTION:

When spraying or applying in any circumstances likely to produce airborne levels of solvent vapors in excess of the TLV, use an organic vapor cartridge or air-supplied respirator.

EYE PROTECTION:

Chemical goggles or full-face shield.

SKIN PROTECTION:

Solvent resistant gloves.

GENERAL:

Safety shower, eye wash station and washing facilities should be available. When using in circumstances where skin contact is likely, use complete protective garments.  
-----

-----  
MATERIAL SAFETY DATA SHEET

PR-1826 Adhesion Promoter (RW-3789-44)  
EM5556

Effective Date: 07/08/03  
-----

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES  
-----

Appearance:	Clear
Physical State:	Liquid
Low Boiling Point:	N/Av
High Boiling Point:	N/Av
Evaporation Rate:	Faster than n-butyl acetate
Vapor Density:	Heavier than air
% Volatiles by Volume:	98
Specific Gravity:	0.82
Liquid Density:	Lighter than water
Weight Per Gallon:	6.8
VOC (GR/L):	784
VOC (GR/L, Combined):	N/App

-----

SECTION X - STABILITY AND REACTIVITY  
-----

STABILITY:

Stable.

HAZARDOUS POLYMERIZATION:

Will not occur.

INCOMPATIBILITY:

Strong oxidizing agents.

CONDITIONS TO AVOID:

See incompatibilities above.

HAZARDOUS DECOMPOSITION PRODUCTS:

Products of combustion are hazardous including carbon monoxide,  
carbon dioxide, and oxides of nitrogen.  
-----

-----  
MATERIAL SAFETY DATA SHEET

PR-1826 Adhesion Promoter (RW-3789-44)  
EM5556

Effective Date: 07/08/03  
-----

SECTION XI - TOXICOLOGICAL INFORMATION  
-----

ACUTE ORAL, DERMAL AND INHALATION EFFECTS (LD50 AND LC50):

CAS NUMBER	LD50	LC50
000078-93-3	2740 mg/kg, oral, rat	11700 ppm, rat, 4hr.
000067-63-0	4710 mg/kg, oral, rat	17000 ppm, rat, 4hr.
REF00000125	N/Av	N/Av
003388-04-3	12300 mg/kg, oral, rat	N/AV.
000090-72-2	1200 mg/kg, oral, rat	N/AV.
028470-78-2	N/AV.	N/AV.

-----

NOTICE:

There are no data available on the product itself.  
-----

SECTION XII - ECOLOGICAL INFORMATION  
-----

NOTICE:

There are no data available on the product itself.  
-----

SECTION XIII - DISPOSAL CONSIDERATIONS  
-----

WASTE DISPOSAL METHOD:

When disposing of this material, ensure that it is packaged, stored, transported, and otherwise handled in accordance with local, state, and federal regulations.

EPA WASTE NUMBERS:

D-001 (Ignitable)  
-----

-----  
MATERIAL SAFETY DATA SHEET

PR-1826 Adhesion Promoter (RW-3789-44)  
FM5556

Effective Date: 07/08/03

-----  
SECTION XIV - TRANSPORT INFORMATION  
-----

DOT (Non-Bulk):  
PROPER SHIPPING NAME: Flammable liquid, n.o.s.,  
TECHNICAL NAMES: Methyl ethyl ketone  
Isopropyl alcohol  
HAZARD CLASS: 3  
UN NUMBER: UN 1993  
PACKING GROUP: II  
LABEL: Flammable liquid  
SPECIAL NOTES:  
None

-----  
SECTION XV - REGULATORY INFORMATION  
-----

TSCA Section 8(b) - Inventory Status:

This product contains an ingredient that is exempt from listing under "Low Volume Exemption" (LVE) and all other ingredients are listed in the TSCA Inventory. This product is governed by the "LVE" and is used only as an adhesion promoter for sealants and substrate.

CANADIAN EPA - DSL Inventory Status:

Contains components not listed on the DSL or NDSL.

SARA Title III Section 313 - Toxic Chemical List (TCL):

This product contains a toxic chemical for routine annual "Toxic Chemical Release Reporting" under Section 313 (40 CFR 372). This information must be included in all MSDS's copied or distributed for this product.

000067-63-0 Isopropanol  
000078-93-3 Methyl Ethyl Ketone

SARA Title III Section 302 - CERCLA:

This product contains the following chemicals regulated under Section 302 as extremely hazardous substance(s) for emergency release notification (CERCLA List).

-----  
MATERIAL SAFETY DATA SHEET

PR-1826 Adhesion Promoter (RW-3789-44)  
FM5556

Effective Date: 07/08/03  
-----

000078-93-3 Methyl Ethyl Ketone

5000

CALIFORNIA PROPOSITION 65 - Reportable ingredients:

Chemicals known by the state of CA to cause cancer:

This product does not contain any chemicals currently on the California list of known carcinogens.

Chemicals known by the state of CA to cause reproductive toxicity:

This product does not contain any chemicals currently on the California list of known Reproductive Toxins.

TSCA Section 12(b) - Export Notification:

This product contains following chemical that required annual or one time export notification per chemical and per country.

000067-63-0 Isopropanol

CLEAN AIR ACT - Hazardous Air Pollutants (CAA Section 112):

This product contains the following chemicals regulated under Section 112 for National Emission Standards of Hazardous Air Pollutants notification.

000078-93-3 Methyl Ethyl Ketone

Pennsylvania Right to Know - Reportable Ingredients:

The following is required composition information. Also, review Section II for additional information for other chemicals.

000067-63-0 Isopropanol

000078-93-3 Methyl Ethyl Ketone

New Jersey Right to Know - Reportable Ingredients:

The following is required composition information. Also, review Section II for additional information for other chemicals.

000067-63-0 Isopropanol

000078-93-3 Methyl Ethyl Ketone  
-----

---

MATERIAL SAFETY DATA SHEET

PR-1826 Adhesion Promoter (RW-3789-44)  
FM5556

Effective Date: 07/08/03

---

SECTION XVI - OTHER INFORMATION

---

Effective Date: 07/08/03      Supersedes Date: 06/05/2003  
Revision Number: 03  
Revision Reason: Update Section 15

The information in this MSDS was obtained from sources which we believe to be reliable. However, since much of the information has been received from sources outside the company, it is provided without any warranty, expressed or implied, regarding its correctness, or suitability for specific situations. The conditions of handling, storage, use, and disposal of this product are beyond our control and may be beyond our knowledge. The user has the sole responsibility to determine the suitability of the material for any use, and the manner and conditions of use. Therefore, we cannot assume responsibility and expressly disclaim liability for loss, damage, injury, or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. Effects can be aggravated by other materials and/or this material may aggravate or add to the effects of other materials.

---

End of Document

MATERIAL SAFETY DATA SHEET

PR-1826 B-1/2, Part A  
FM5352A

Effective Date: 01/15/01

SECTION I - MANUFACTURER AND PRODUCT INFORMATION

PRC-DeSoto International, Inc.  
A PPG Industries Company  
5430 San Fernando Road  
P.O. Box 1800  
Glendale, CA 91209

Information Phone: (818) 240-2060  
Emergency Phone: (800) 228-5635  
CHEMTREC: (800) 424-9300

Trade Name: PR-1826 B-1/2, Part A  
Accelerator component  
Product Code: FM5352A  
Form ID No: X04  
Product Class: Filled epoxy resins mixture  
Synonyms: S-5352

HMIS HAZARD RATING  
HEALTH - 2  
FLAMMABILITY - 1  
REACTIVITY - 0  
PPE - H  
None(0)--->Extreme(4)

SECTION II - COMPOSITION

INGREDIENTS INFORMATION

CAS NUMBER	Wt %	CHEMICAL IDENTITY
025068-38-6	30 - 60	Bisphenol, A/Epichlorohydrin Based Epoxy Resin
028064-14-4	10 - 30	Polymer of Epichlorohydrin, Phenol-Formaldehyde Nov
001317-65-3	10 - 30	Limestone
000471-34-1	10 - 30	Calcium Carbonate
001333-86-4	1 - 10	Carbon Black
002530-83-8	< 5	Gamma-Glycidoxypropyltrimeth- oxysilane

EXPOSURE LIMITS

EXPOSURE LIMITS (ppm)

CAS NUMBER	ACGIH TLVs		OSHA PELs		
	TWA	STEL	TWA	STEL	
025068-38-6	N/E	N/E	N/E	N/E	
028064-14-4	N/E	N/E	N/E	N/E	
001317-65-3	10 mg/m3	N/E	N/E	N/E	S
000471-34-1	10	N/E	15	N/E	S
001333-86-4	3.5 mg/m3	N/E	3.5 mg/m3	N/E	S
002530-83-8	N/E	N/E	N/E	N/E	

Footnotes

- (S) Occupational Exposure Standard
- (R) Supplier's Recommended Limit

-----  
MATERIAL SAFETY DATA SHEET

PR-1826 B-1/2, Part A  
FM5352A

Effective Date: 01/15/01

-----  
N/Av = Not Available                      N/Ap = Not Applicable  
N.E. = Not Established                    NotknownXXX = CAS Number is not known.  
-----

SECTION III - HAZARDS IDENTIFICATION

-----  
Permissible Exposure Limits for Product:  
Not established for product. See Section II.

ROUTE OF ENTRY AND EFFECTS OF OVEREXPOSURE

ROUTE OF ENTRY:

Inhalation and dermal.

INHALATION:

Vapor or fume will irritate the nose and throat.

EYE CONTACT:

Vapor or fume can irritate the eyes.

SKIN CONTACT:

Substance can cause moderate irritation.

INGESTION:

Ingestion can cause irritation of gastro-intestinal tract.

Contains an ingredient listed as known or suspected carcinogen?

NTP: No                      OSHA: No                      IARC: Yes

-----  
SECTION IV - FIRST AID MEASURES

-----  
INHALATION:

If inhaled, remove from area to fresh air. If not breathing, give artificial respiration. Get immediate medical attention. If breathing is difficult, transport to medical facility and, if available, give supplemental oxygen.

EYE CONTACT:

For eye contact, immediately flush eyes for at least 15 minutes with running water. Hold eyelids apart to ensure rinsing of the entire eye surface and lids with water. Get immediate medical attention.

SKIN CONTACT:

For skin contact, wipe excess material with dry towel. Then wash exposed areas with plenty of water, and soap if available, for several minutes. Get medical attention if irritation occurs.

INGESTION:

If swallowed dilute by giving two(2) glasses of water to drink. Get

-----  
MATERIAL SAFETY DATA SHEET

PR-1826 B-1/2, Part A  
FM5352A

Effective Date: 01/15/01  
-----

immediate medical attention. Never give anything by mouth to an unconscious person.

GENERAL:

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.  
-----

SECTION V - FIRE AND EXPLOSION HAZARD IDENTIFICATION  
-----

FLASHPOINT: N/App Method: Not Applicable

LEL (%): N/Av UEL (%): N/Av

FLAMMABILITY CLASSIFICATION:

Not flammable.

FIRE AND EXPLOSION HAZARDS:

Decomposition and combustion products may be hazardous. No unusual hazards known.

EXTINGUISHING MEDIA:

Carbon dioxide, dry chemical, foam, water fog.

FIRE FIGHTING PROCEDURES:

Use complete personal protection. Use water to cool heat exposed containers.  
-----

SECTION VI - ACCIDENTAL RELEASE MEASURES  
-----

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Cover with absorbent material if necessary. Scoop into containers. Clean up residue with a suitable cleaning solvent. Wear appropriate personal protective equipment (See Section VIII).  
-----

SECTION VII - HANDLING AND STORAGE  
-----

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Keep container tightly closed. Store in a dry location. Wear proper personal protective equipment (See Section VIII). Wash thoroughly after handling and before smoking or eating.  
-----

-----  
MATERIAL SAFETY DATA SHEET

PR-1826 B-1/2, Part A  
FM5352A

Effective Date: 01/15/01  
-----

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION  
-----

ENGINEERING CONTROLS:

Good general mechanical ventilation.

RESPIRATORY PROTECTION:

Not normally required.

EYE PROTECTION:

Safety glasses.

SKIN PROTECTION:

Chemically resistant gloves.

GENERAL:

Safety shower, eye wash station and washing facilities should be available. When using in circumstances where skin contact is likely, use complete protective garments.  
-----

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES  
-----

Appearance:	Black
Physical State:	Paste
Low Boiling Point:	N/Av
High Boiling Point:	N/Av
Evaporation Rate:	Non-volatile
Vapor Density:	Non-volatile
% Volatiles by Volume:	0
Specific Gravity:	1.36
Liquid Density:	Heavier than water
Weight Per Gallon:	11.33
VOC (GR/L):	0
VOC (GR/L, Combined):	N/Av

  
-----

SECTION X - STABILITY AND REACTIVITY  
-----

STABILITY:

Stable.

HAZARDOUS POLYMERIZATION:

Will not occur.

INCOMPATIBILITY:

Strong oxidizing agents, amines, bases, alkalis.  
-----

-----  
MATERIAL SAFETY DATA SHEET

PR-1826 B-1/2, Part A  
FM5352A

Effective Date: 01/15/01  
-----

CONDITIONS TO AVOID:

See incompatibilities above.

HAZARDOUS DECOMPOSITION PRODUCTS:

Oxides of carbon.  
-----

SECTION XI - TOXICOLOGICAL INFORMATION  
-----

ACUTE ORAL, DERMAL AND INHALATION EFFECTS (LD50 AND LC50):

CAS NUMBER	LD50	LC50
025068-38-6	11400 mg/kg, oral, rat	N/AV.
028064-14-4	4000 mg/kg, oral, rat	N/AV.
001317-65-3	6450 mg/kg, oral, rat	N/AV.
000471-34-1	2000 mg/kg, oral, rat	N/AV.
001333-86-4	440 mg/kg, oral, rat	6750 mg/m3, rat, 4hr.
002530-83-8	23000 mg/kg, oral, rat	N/AV.

-----

Carcinogenicity:

Carbon Black:

Based on an IARC conclusion that there is "sufficient evidence in experimental animals for the carcinogenicity of carbon black" and inadequate evidence of carcinogenicity in humans. IARC's overall evaluation is that "carbon black is possibly carcinogenic to humans" (Group 2B).

Carbon black has not been listed as a carcinogen by National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety & Health (NIOSH) criteria document on carbon black recommends that only carbon blacks with PAH levels greater than 0.1% be considered suspect carcinogens.

NOTICE:

There are no data available on the product itself.  
-----

MATERIAL SAFETY DATA SHEET

PR-1826 B-1/2, Part A  
FM5352A

Effective Date: 01/15/01

SECTION XII - ECOLOGICAL INFORMATION

NOTICE:

There are no data available on the product itself.

SECTION XIII - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD:

When disposing of this material, ensure that it is packaged, stored, transported, and otherwise handled in accordance with local, state, and federal regulations.

SECTION XIV - TRANSPORT INFORMATION

DOT (Non-Bulk):

PROPER SHIPPING NAME: Not regulated  
HAZARD CLASS: Not Applicable  
UN NUMBER: Not Available

SPECIAL NOTES:

None

SECTION XV - REGULATORY INFORMATION

TSCA Section 8(b) - Inventory Status:

All ingredients in this product are listed in the TSCA Inventory or are exempt from listing.

CANADIAN EPA - DSL Inventory Status:

The DSL status of this product is unknown at this time.

SARA Title III Section 313 - Toxic Chemical List (TCL):

This product does not contain a toxic chemical for routine annual "Toxic Chemical Release Reporting" under Section 313 (40 CFR 372).

-----  
MATERIAL SAFETY DATA SHEET

PR-1826 B-1/2, Part A  
FM5352A

Effective Date: 01/15/01  
-----

SECTION XVI - OTHER INFORMATION  
-----

Effective Date: 01/15/01      Supersedes Date: 03/02/1999  
Revision Number: 01

The information in this MSDS was obtained from sources which we believe to be reliable. However, since much of the information has been received from sources outside the company, it is provided without any warranty, expressed or implied, regarding its correctness, or suitability for specific situations. The conditions of handling, storage, use, and disposal of this product are beyond our control and may be beyond our knowledge. The user has the sole responsibility to determine the suitability of the material for any use, and the manner and conditions of use. Therefore, we cannot assume responsibility and expressly disclaim liability for loss, damage, injury, or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. Effects can be aggravated by other materials and/or this material may aggravate or add to the effects of other materials.

-----

End of Document

-----  
MATERIAL SAFETY DATA SHEET

PR-1826 B-1/2, Part B  
FM3560

Effective Date: 01/24/01

-----  
SECTION I - MANUFACTURER AND PRODUCT INFORMATION  
-----

PRC-DeSoto International, Inc.  
A PPG Industries Company  
5430 San Fernando Road  
P.O. Box 1800  
Glendale, CA 91209

Information Phone: (818) 240-2060  
Emergency Phone: (800) 228-5635  
CHEMTREC: (800) 424-9300

Trade Name: PR-1826 B-1/2, Part B  
Base component  
Product Code: FM3560  
Form ID No: A13  
Product Class: Filled polythioether  
Synonyms: P-3560

HMIS HAZARD RATING  
HEALTH - 2  
FLAMMABILITY - 2  
REACTIVITY - 0  
PPE - H  
None(0)--->Extreme(4)

-----  
SECTION II - COMPOSITION  
-----

INGREDIENTS INFORMATION

CAS NUMBER	Wt %	CHEMICAL IDENTITY
119147-78-3	30 - 60	Mercaptan Terminated Polythioether
000471-34-1	10 - 30	Calcium Carbonate
021645-51-2	1 - 10	Aluminum Hydroxide
067762-90-7	< 5	Amorphous Fumed Silica
000078-93-3	< 5	Methyl Ethyl Ketone
013463-67-7	< 5	Titanium Dioxide @

EXPOSURE LIMITS

CAS NUMBER	EXPOSURE LIMITS (ppm)				
	ACGIH TLVs		OSHA PELs		
	TWA	STEL	TWA	STEL	
119147-78-3	N/E	N/E	N/E	N/E	
000471-34-1	10	N/E	15	N/E	S
021645-51-2	2 mg/m3	N/E	N/E	N/E	
067762-90-7	10 mg/m3	N/E	N/E	N/E	S
000078-93-3	200	300	200	300	S
013463-67-7	10 mg/m3	N/E	10 mg/m3	N/E	S

Footnotes

(S) Occupational Exposure Standard  
(R) Supplier's Recommended Limit

-----  
MATERIAL SAFETY DATA SHEET

PR-1826 B-1/2, Part B  
FM3560

Effective Date: 01/24/01  
-----

N/Av = Not Available

N/Ap = Not Applicable

N.E. = Not Established

NotknownXXX = CAS Number is not known.  
-----

SECTION III - HAZARDS IDENTIFICATION  
-----

Permissible Exposure Limits for Product:

Not established for product. See Section II.

ROUTE OF ENTRY AND EFFECTS OF OVEREXPOSURE

ROUTE OF ENTRY:

Inhalation and dermal.

INHALATION:

Vapor and mist will irritate nose, throat and respiratory tract.  
High vapor concentration may cause dizziness, drowsiness and  
fatigue.

EYE CONTACT:

Vapor, mist or liquid is severely irritating to eyes and cause  
blurred vision, redness and tearing.

SKIN CONTACT:

Liquid can cause severe skin irritation with drying, defatting,  
splitting and cracking on repeated contact.

INGESTION:

Liquid can cause irritation of gastro-intestinal tract followed by  
nausea and vomiting, abdominal discomfort, and rapid pulse.

DELAYED EFFECTS:

Repeated overexposure may cause central nervous systems depression,  
and kidney/liver damage.

Contains an ingredient listed as known or suspected carcinogen?

NTP: No

OSHA: No

IARC: No  
-----

SECTION IV - FIRST AID MEASURES  
-----

INHALATION:

If inhaled, remove from area to fresh air. If not breathing, give  
artificial respiration. Get immediate medical attention. If  
breathing is difficult, transport to medical facility and, if  
available, give supplemental oxygen.

EYE CONTACT:

For eye contact, immediately flush eyes for at least 15 minutes  
with running water. Hold eyelids apart to ensure rinsing of the  
-----

-----  
MATERIAL SAFETY DATA SHEET

PR-1826 B-1/2, Part B  
FM3560

Effective Date: 01/24/01  
-----

entire eye surface and lids with water. Get immediate medical attention.

SKIN CONTACT:

For skin contact, wipe excess material with dry towel. Then wash exposed areas with plenty of water, and soap if available, for several minutes. Get medical attention if irritation occurs.

INGESTION:

If swallowed dilute by giving two(2) glasses of water to drink. Get immediate medical attention. Never give anything by mouth to an unconscious person.

GENERAL:

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.  
-----

SECTION V - FIRE AND EXPLOSION HAZARD IDENTIFICATION  
-----

FLASHPOINT: 150 F 65.55 C Method: Setaflash  
LEL (%): 1.8 UEL (%): N/Av

FLAMMABILITY CLASSIFICATION:

Combustible

FIRE AND EXPLOSION HAZARDS:

Decomposition and combustion products may be hazardous. High temperatures may cause pressure build-up in closed containers. Vapors may accumulate in inadequately ventilated or confined areas. Vapors may form explosive mixture with air. Vapors are heavier than air and may travel long distances. Flashback or flame to the handling site may occur. Closed containers may explode when exposed to extreme heat.

EXTINGUISHING MEDIA:

Carbon dioxide, dry chemical, foam.

FIRE FIGHTING PROCEDURES:

Water spray may be ineffective. Cool fire exposed containers with water. Fog nozzles are preferable. Wear NIOSH/MSHA approved self-contained breathing apparatus and complete protective clothing to prevent contact with skin and eyes.  
-----

-----  
MATERIAL SAFETY DATA SHEET

PR-1826 B-1/2, Part B  
FM3560

Effective Date: 01/24/01  
-----

SECTION VI - ACCIDENTAL RELEASE MEASURES  
-----

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Remove all ignition sources. Wear an air-supplied respirator for an unventilated spill. Cover with absorbent. Scoop into containers using non-sparking tools. Clean up residue with a suitable cleaning solvent. Wear appropriate personal protective equipment (See Section VIII).  
-----

SECTION VII - HANDLING AND STORAGE  
-----

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Keep container tightly closed. Isolate from heat, electrical equipment, sparks and flame. Use grounding and bonding procedures during transfer. Do not store above 120 degrees F. Vapors of this product are heavier than air and may collect in low or confined areas. Empty drums may contain explosive vapors. Do not cut, puncture, or weld on or near drum. Wear proper personal protective equipment (See Section VIII). Wash thoroughly after handling and before smoking or eating.  
-----

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION  
-----

ENGINEERING CONTROLS:

RESPIRATORY PROTECTION:

When spraying or applying in any circumstances likely to produce airborne levels of solvent vapors in excess of the TLV, use an organic vapor cartridge or air-supplied respirator.

EYE PROTECTION:

Safety glasses.

SKIN PROTECTION:

Solvent resistant gloves.

GENERAL:

Safety shower, eye wash station and washing facilities should be available. When using in circumstances where skin contact is likely, use complete protective garments.  
-----

-----  
MATERIAL SAFETY DATA SHEET

PR-1826 B-1/2, Part B  
FM3560

Effective Date: 01/24/01  
-----

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES  
-----

Appearance: White  
Physical State: Thixotropic paste  
Low Boiling Point: 175 F 79.44 C  
High Boiling Point: N/Av  
Evaporation Rate: Unknown  
Vapor Density: Heavier than air  
% Volatiles by Volume: 5.5  
Specific Gravity: 1.45  
Liquid Density: Heavier than water  
Weight Per Gallon: 12.08  
VOC (GR/L): N/Av  
VOC (GR/L, Combined): 46  
-----

SECTION X - STABILITY AND REACTIVITY  
-----

STABILITY:

Stable.

HAZARDOUS POLYMERIZATION:

Will not occur.

INCOMPATIBILITY:

Strong oxidizing agents.

CONDITIONS TO AVOID:

See incompatibilities above.

HAZARDOUS DECOMPOSITION PRODUCTS:

Oxides of carbon and nitrogen, sulfur dioxide, traces of hydrogen sulfide.  
-----

SECTION XI - TOXICOLOGICAL INFORMATION  
-----

-----  
MATERIAL SAFETY DATA SHEET

PR-1826 B-1/2, Part B  
FM3560

Effective Date: 01/24/01  
-----

ACUTE ORAL, DERMAL AND INHALATION EFFECTS (LD50 AND LC50):

CAS NUMBER	LD50	LC50
119147-78-3	5000 mg/kg, orl, rat	N/AV.
000471-34-1	2000 mg/kg, oral, rat	N/AV.
021645-51-2	N/AV.	N/AV.
067762-90-7	5000 mg/kg, oral, rat	4.9 mg/L, rat, 4hr.
000078-93-3	2740 mg/kg, oral, rat	11700 ppm, rat, 4hr.
013463-67-7	7500 mg/kg, oral, rat	N/AV.

-----

NOTICE:

There are no data available on the product itself.  
-----

SECTION XII - ECOLOGICAL INFORMATION  
-----

NOTICE:

There are no data available on the product itself.  
-----

SECTION XIII - DISPOSAL CONSIDERATIONS  
-----

WASTE DISPOSAL METHOD:  
-----

SECTION XIV - TRANSPORT INFORMATION  
-----

DOT (Non-Bulk):

PROPER SHIPPING NAME: Not regulated  
HAZARD CLASS: Not Applicable  
UN NUMBER: Not Available

SPECIAL NOTES:

None  
-----

-----  
MATERIAL SAFETY DATA SHEET

PR-1826 B-1/2, Part B  
FM3560

Effective Date: 01/24/01  
-----

SECTION XV - REGULATORY INFORMATION  
-----

TSCA Section 8(b) - Inventory Status:

All ingredients in this product are listed in the TSCA Inventory or are exempt from listing.

CANADIAN EPA - DSL Inventory Status:

The DSL status of this product is unknown at this time.

SARA Title III Section 313 - Toxic Chemical List (TCL):

This product contains a toxic chemical for routine annual "Toxic Chemical Release Reporting" under Section 313 (40 CFR 372). This information must be included in all MSDS's copied or distributed for this product.

000078-93-3 Methyl Ethyl Ketone

SARA Title III Section 302 - CERCLA:

This product contains the following chemicals regulated under Section 302 as extremely hazardous substance(s) for emergency release notification (CERCLA List).

000078-93-3 Methyl Ethyl Ketone

5000

CALIFORNIA PROPOSITION 65 - Reportable ingredients:

Chemicals known by the state of CA to cause cancer:

This product does not contain any chemicals currently on the California list of known carcinogens.

Chemicals known by the state of CA to cause reproductive toxicity:

This product does not contain any chemicals currently on the California list of known Reproductive Toxins.

TSCA Section 12(b) - Export Notification:

This product does not contain any chemicals subject to Section 12(b) export notification.

CLEAN AIR ACT - Hazardous Air Pollutants (CAA Section 112):

This product contains the following chemicals regulated under Section 112 for National Emission Standards of Hazardous Air

-----  
MATERIAL SAFETY DATA SHEET

PR-1826 B-1/2, Part B  
FM3560

Effective Date: 01/24/01  
-----

Pollutants notification.

000078-93-3 Methyl Ethyl Ketone

Pennsylvania Right to Know - Reportable Ingredients:

The following is required composition information. Also, review Section II for additional information for other chemicals.

000078-93-3 Methyl Ethyl Ketone  
013463-67-7 Titanium Dioxide @

New Jersey Right to Know - Reportable Ingredients:

The following is required composition information. Also, review Section II for additional information for other chemicals.

000078-93-3 Methyl Ethyl Ketone  
013463-67-7 Titanium Dioxide @

-----  
SECTION XVI - OTHER INFORMATION  
-----

Effective Date: 01/24/01      Supersedes Date: 11/08/1993  
Revision Number: 01

The information in this MSDS was obtained from sources which we believe to be reliable. However, since much of the information has been received from sources outside the company, it is provided without any warranty, expressed or implied, regarding its correctness, or suitability for specific situations. The conditions of handling, storage, use, and disposal of this product are beyond our control and may be beyond our knowledge. The user has the sole responsibility to determine the suitability of the material for any use, and the manner and conditions of use. Therefore, we cannot assume responsibility and expressly disclaim liability for loss, damage, injury, or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. Effects can be aggravated by other materials and/or this material may aggravate or add to the effects of other materials.

-----  
End of Document