Material Safety Data Sheet



Date of issue 19 June 2016

7

Version

Product and company identification 1.

Product name	: PR 1535 AMB Part A
Code	: PR 1535 AMB Part A
Manufacturer / Supplier	: PPG Aerospace PRC-DeSoto 12780 San Fernando Road Sylmar, CA 91342 Phone: 818 362 6711
Emergency telephone number	: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) 01-800-00-21-400 (Mexico)

Emergency overview	: WARNING!
	HARMFUL IF INHALED. CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. MAY BE HARMFUL IF ABSORBED THROUGH SKIN OR IF SWALLOWED. CONTAINS MATERIAL THAT CAN CAUSE TARGET ORGAN DAMAGE. CANCER HAZARD - CONTAINS MATERIAL WHICH CAN CAUSE CANCER.
	Do not breathe vapor or mist. Do not swallow. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.
Potential acute health effects	
Inhalation	: Harmful if inhaled. Irritating to respiratory system. Can irritate eyes, nose, mouth and throat. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
Ingestion	: May be harmful if swallowed.
Skin	: Harmful in contact with skin. Irritating to skin.
Eyes	: Irritating to eyes.

Based on the properties of the isocyanate components and considering toxicological data on similar mixtures, this mixture may cause acute irritation and/or sensitization of the respiratory system, leading to an asthmatic condition, wheezing and tightness of the chest. Sensitized persons may subsequently show asthmatic symptoms when exposed to atmospheric concentrations well below the OEL. Repeated exposure may lead to permanent respiratory disability.

Medical conditions	: Pre-existing dis
aggravated by over-	risk may be ag
ovnocuro	

sorders involving any target organs mentioned in this MSDS as being at gravated by over-exposure to this product.

exposure

This Material Safety Data Sheet has been prepared in accordance with Canada's Workplace Hazardous Materials Information System (WHMIS).

See toxicological information (Section 11)

CAS number

101-14-4

8001-79-4 9069-50-5 % (w/w)

15 - 40 10 - 30

10 - 30

Product name PR 1535 AMB Part A

3. Composition/information on ingredients

<u>Name</u>

2,2'-dichloro-4,4'-methylenedianiline
Castor oil
Poly(oxy-1,4-butanediyl), α-hydro-ω-hydroxy-, polymer with 1,3-
diisocyanatomethylbenzene

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Material Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Eye contact	 Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Ingestion	 If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

5. Fire-fighting measures

Flammability of the product Extinguishing media	fire or if heated, a press	ure increase will occur and the container may burst.
Suitable	e an extinguishing agent	suitable for the surrounding fire.
Not suitable	ne known.	
Special exposure hazards	e is a fire. No action sha ning. Fire water contami	y removing all persons from the vicinity of the incident if all be taken involving any personal risk or without suitable nated with this material must be contained and prevented y waterway, sewer or drain.
Hazardous combustion products	composition products may bon oxides ogen oxides ogenated compounds Irogen cyanide (HCN). unate and isocyanate.	y include the following materials:
Special protective equipment for fire-fighters		propriate protective equipment and self-contained breathing face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions: No action shall be taken involving any personal risk or without suitable training.
Evacuate surrounding areas. Keep unnecessary and unprotected personnel from
entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist.
Provide adequate ventilation. Wear appropriate respirator when ventilation is
inadequate. Put on appropriate personal protective equipment (see Section 8).

Product name PR 1535 AMB Part A

6. Accidental release measures

Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental
	pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to
	the environment if released in large quantities.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

7. Handling and storage

Handling Put on appropriate personal protective equipment (see Section 8). Eating, drinking and 5 smoking should be prohibited in areas where this material is handled, stored and processed. Do not breathe vapor or mist. Do not swallow. Do not get in eyes or on skin or clothing. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. If this material is part of a multiple component system, read the Material Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts. Store in accordance with local regulations. Store in original container protected from **Storage** ŝ,

direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Do not store below the following temperature: 32F / 0C.

Exposure controls/personal protection 8.

Name	Result	ACGIH	Ontario	Mexico	PPG
2,2'-dichloro-4,4'-methylenedianiline	TWA	0.01 ppm S	0.0005 ppm S	0.01 ppm S	Not established
Poly(oxy-1,4-butanediyl), α-hydro-ω- hydroxy-, polymer with 1,3- diisocyanatomethylbenzene	TWA	0.005 ppm	Not established	Not established	Not established
disocyanalometryibenzene	STEL	0.02 ppm	Not established	Not established	Not established

Key to abbreviations

= Acceptable Maximum Peak A ACGIH = American Conference of Governmental Industrial Hygienists. = Ceiling Limit С F = Fume IPEL = Internal Permissible Exposure Limit = Respirable R S = Potential skin absorption

- SR = Respiratory sensitization
- SS = Skin sensitization
- STEL = Short term Exposure limit values TD
 - = Total dust
- TLV = Threshold Limit Value
- = Time Weighted Average TWA
- Consult local authorities for acceptable exposure limits.

Product name PR 1535 AMB Part A

8. Exposure controls/personal protection

Recommended monitoring procedures	:	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of
Engineering measures	:	hazardous substances will also be required. Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Personal protection		
Eyes		Safety glasses with side shields.
Hands		Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves		butyl rubber
Respiratory		If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Skin	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Restrictions on use	:	Persons with a history of asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used.

9. Physical and chemical properties

		Canada - Mexico	Page: 4/7
Evaporation rate	: Not available.		
Vapor density	: Not available.		
Vapor pressure	: Not available.		
Density(lbs / gal)	: 8.93		
Specific gravity	: 1.07		
Melting/freezing point	: Not available.		
Boiling/condensation point	: >37.78°C (>100°F)		
рН	: Not available.		
Odor	: Not available.		
Color	: Amber.		
Material supports combustion.	: Yes.		
Flash point	: Closed cup: Not applicable.		
Physical state	: Liquid.		

Product name PR 1535 AMB Part A

Physical and chemical properties 9.

VOC

VOC	:	0
Solubility	÷	Insoluble in the following materials: cold water.
Partition coefficient: n-	\$	Not available.
octanol/water		
% Solid. (w/w)	\$	100

10. Stability and reactivity

Stability	: Stable under recommended storage and handling conditions (see Section 7).
Conditions to avoid	: No specific data.
Materials to avoid	: Reactive or incompatible with the following materials:,oxidizing materials,strong acids, strong alkalis
Hazardous decomposition products	: Cyanate and isocyanate.
Hazardous polymerization	: Under normal conditions of storage and use, hazardous polymerization will not occur.

11. Toxicological information

Acute toxicity

Product/ingredient name		Result	Species	Dose	Exposure
2,2'-dichloro-4,4'-methylenedianiline		LD50 Oral	Rat	750 mg/kg	-
		LD50 Dermal	Rabbit	>5000 mg/kg	-
Castor oil		LD50 Oral	Rat	10 g/kg	-
Conclusion/Summary Chronic toxicity	: Not availa	ble.			
Conclusion/Summary	: Not availa	ble.			
ärget organs	nervous s Contains i	ystem (CNS).	cause damage t	e following organs: s o the following orgar	
arcinogenicity					
carcinogenicity carcinogenicity			cause cancer. R	isk of cancer depend	ds on duration and
	: Contains r level of ex		cause cancer. R	isk of cancer depend	ds on duration and
Carcinogenicity	level of ex		cause cancer. R	isk of cancer depend	
arcinogenicity	level of ex	posure.		Re to l	

Product name PR 1535 AMB Part A

12. Ecological information

Environmental effects

Water polluting material. May be harmful to the environment if released in large ŝ, quantities.

13. Disposal considerations

Waste disposal	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
----------------	--

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

	TDG	Mexico	IMDG
UN number	UN3082	UN3082	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,2'-dichloro-4,4'- methylenedianiline)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,2'-dichloro-4,4'- methylenedianiline)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,2'-dichloro-4,4'- methylenedianiline)
Transport hazard class(es)	9	9	9
Packing group	III	III	III
Environmental hazards	Yes.	Yes.	Yes.
Marine pollutant substances	(2,2'-dichloro-4,4'- methylenedianiline)	Not applicable.	(2,2'-dichloro-4,4'- methylenedianiline)

14. Transport information

Additional information

TDG	 Non-bulk packages of this product are not regulated as dangerous goods when transported by road or rail.
Mexico	: The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or

≤5 kg. : This product is not regulated as a dangerous good when transported in sizes of ≤ 5 L or ≤ 5 kg, IMDG provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Product name PR 1535 AMB Part A

14. Transport information

Proof of classification statement	 Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.43-2.45 (Class 9), 2.7 (Marine pollutant mark). 				
15. Regulatory information					
anada inventory (DSL) : All components are listed or exempted.					
<u>Canada</u> WHMIS (Canada)	: Class D-1B: Material causing immediate and serious toxic effects (Toxic). Class D-2A: Material causing other toxic effects (Very toxic). Class D-2B: Material causing other toxic effects (Toxic).				
<u>Mexico</u> Classification Flammability : 0 He	ealth : 3 Reactivity : 0				

16. Other information

Hazardous Material Information System (U.S.A.)

Health : 3 * Flammability : 0 Physical hazards : 0 (*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)Health : 3Flammability : 0Instability : 0Instability : 0Date of previous issue: 5/19/2016Organization that prepared: EHSthe MSDS

✓ Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.