

# DOW CORNING CORPORATION

## Material Safety Data Sheet

Page: 1 of 7

Version: 1.4

Revision Date: 2009/06/19

### MOLYKOTE(R) 33 LIGHT EXTREME LOW TEMPERATURE GREASE

#### 1. PRODUCT AND COMPANY IDENTIFICATION

Dow Corning Corporation  
South Saginaw Road  
Midland, Michigan 48686

**24 Hour Emergency Telephone: (989) 496-5900**

Customer Service: (989) 496-6000

Product Disposal Information: (989) 496-6315

CHEMTREC: (800) 424-9300

MSDS No.: 04016015

Revision Date: 2009/06/19

Generic Description: Silicone grease.

Physical Form: Grease

Color: White

Odor: Slight odor

NFPA Profile: Health 1 Flammability 1 Instability/Reactivity 0

Note: NFPA = National Fire Protection Association

#### 2. HAZARDS IDENTIFICATION

##### POTENTIAL HEALTH EFFECTS

##### Acute Effects

Eye: Direct contact may cause temporary redness and discomfort.

Skin: No significant irritation expected from a single short-term exposure.

Inhalation: No significant effects expected from a single short-term exposure.

Oral: Low ingestion hazard in normal use.

##### Prolonged/Repeated Exposure Effects

Skin: Repeated or prolonged exposure may cause irritation.

Inhalation: No known applicable information.

Oral: Repeated ingestion or swallowing large amounts may injure internally.

##### Signs and Symptoms of Overexposure

No known applicable information.

##### Medical Conditions Aggravated by Exposure

No known applicable information.

The above listed potential effects of overexposure are based on actual data, results of studies performed upon similar compositions,

**MOLYKOTE(R) 33 LIGHT EXTREME LOW TEMPERATURE GREASE**

component data and/or expert review of the product. Please refer to Section 11 for the detailed toxicology information.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

None present. This is not a hazardous material as defined in the OSHA Hazard Communication Standard.

**4. FIRST AID MEASURES**

Eye:	Immediately flush with water.
Skin:	Remove from skin and wash thoroughly with soap and water or waterless cleanser. Get medical attention if irritation or other ill effects develop or persist.
Inhalation:	No first aid should be needed.
Oral:	Get medical attention.
Notes to Physician:	Treat according to person's condition and specifics of exposure.

**5. FIRE FIGHTING MEASURES**

Flash Point:	> 214 °F / > 101.1 °C (Closed Cup)
Autoignition Temperature:	Not determined.
Flammability Limits in Air:	Not determined.
Extinguishing Media:	On large fires use dry chemical, foam or water spray. On small fires use carbon dioxide (CO <sub>2</sub> ), dry chemical or water spray. Water can be used to cool fire exposed containers.
Fire Fighting Measures:	Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.
Unusual Fire Hazards:	None.

**6. ACCIDENTAL RELEASE MEASURES**

**MOLYKOTE(R) 33 LIGHT EXTREME LOW TEMPERATURE GREASE**

**Containment/Clean up:** Observe all personal protection equipment recommendations described in Sections 5 and 8. Wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard. Final cleaning may require use of steam, solvents or detergents. Dispose of saturated absorbant or cleaning materials appropriately, since spontaneous heating may occur. Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

**Note:** See section 8 for Personal Protective Equipment for Spills. Call (989) 496-5900, if additional information is required.

**7. HANDLING AND STORAGE**

Use with adequate ventilation. Traces of benzene (carcinogen) may form if heated in air above 300 F (149 C). Provide ventilation to control vapor exposure within inhalation guidelines when handling at elevated temperatures. Review the OSHA benzene regulation for detailed information on safe handling requirements. Avoid eye contact. Avoid skin contact. Do not take internally.

Use reasonable care and store away from oxidizing materials.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Component Exposure Limits**

There are no components with workplace exposure limits.

**Engineering Controls**

Local Ventilation: None should be needed.  
 General Ventilation: Recommended.

**Personal Protective Equipment for Routine Handling**

**Eyes:** Use proper protection - safety glasses as a minimum.

**Skin:** Washing at mealtime and end of shift is adequate.

**Suitable Gloves:** Avoid skin contact by implementing good industrial hygiene practices and procedures. Select and use gloves and/or protective clothing to further minimize the potential for skin contact. Consult with your glove and/or personnel protective equipment manufacturer for selection of appropriate compatible materials.

**Inhalation:** No respiratory protection should be needed.

**MOLYKOTE(R) 33 LIGHT EXTREME LOW TEMPERATURE GREASE**

Suitable Respirator: None should be needed.

**Personal Protective Equipment for Spills**

Eyes: Use proper protection - safety glasses as a minimum.

Skin: Washing at mealtime and end of shift is adequate.

Inhalation/Suitable Respirator: No respiratory protection should be needed.

Precautionary Measures: Avoid eye contact. Avoid skin contact. Do not take internally. Use reasonable care.

Comments: Traces of benzene (carcinogen) may form if heated in air above 300 F (149 C). Provide ventilation to control vapor exposure within inhalation guidelines when handling at elevated temperatures. Review the OSHA benzene regulation for detailed information on safe handling requirements.

Note: These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

Physical Form: Grease

Color: White

Odor: Slight odor

Specific Gravity @ 25°C: 1.1

Viscosity: Not determined.

Freezing/Melting Point: Not determined.

Boiling Point: Not determined.

Vapor Pressure @ 25°C: Not determined.

Vapor Density: Not determined.

Solubility in Water: Not determined.

pH: Not determined.

Volatile Content: Not determined.

Flash Point: > 214 °F / > 101.1 °C (Closed Cup)

Autoignition Temperature: Not determined.

Flammability Limits in Air: Not determined.

Note: The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing specifications.

**10. STABILITY AND REACTIVITY**

Chemical Stability: Stable.

Hazardous Polymerization: Hazardous polymerization will not occur.

**MOLYKOTE(R) 33 LIGHT EXTREME LOW TEMPERATURE GREASE**

Conditions to Avoid: None.

Materials to Avoid: Oxidizing material can cause a reaction.

Hazardous Decomposition Products

Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Carbon oxides and traces of incompletely burned carbon compounds. Silicon dioxide. Metal oxides. Formaldehyde.

**11. TOXICOLOGICAL INFORMATION**Special Hazard Information on Components

No known applicable information.

**12. ECOLOGICAL INFORMATION**Environmental Fate and Distribution

Complete information is not yet available.

Environmental Effects

Complete information is not yet available.

Fate and Effects in Waste Water Treatment Plants

Complete information is not yet available.

## Ecotoxicity Classification Criteria

Hazard Parameters (LC50 or EC50)	High	Medium	Low
Acute Aquatic Toxicity (mg/L)	$\leq 1$	$>1$ and $\leq 100$	$>100$
Acute Terrestrial Toxicity	$\leq 100$	$>100$ and $\leq 2000$	$>2000$

This table is adapted from "Environmental Toxicology and Risk Assessment", ASTM STP 1179, p.34, 1993.

This table can be used to classify the ecotoxicity of this product when ecotoxicity data is listed above. Please read the other information presented in the section concerning the overall ecological safety of this material.

**13. DISPOSAL CONSIDERATIONS**RCRA Hazard Class (40 CFR 261)

When a decision is made to discard this material, as received, is it classified as a hazardous waste? No

State or local laws may impose additional regulatory requirements regarding disposal. Call (989) 496-6315, if additional

**MOLYKOTE(R) 33 LIGHT EXTREME LOW TEMPERATURE GREASE**

information is required.

**14. TRANSPORT INFORMATION****DOT Road Shipment Information (49 CFR 172.101)**

Not subject to DOT.

**Ocean Shipment (IMDG)**

Not subject to IMDG code.

**Air Shipment (IATA)**

Not subject to IATA regulations.

Call Dow Corning Transportation, (989) 496-8577, if additional information is required.

**15. REGULATORY INFORMATION**

Contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA Status: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

**EPA SARA Title III Chemical Listings****Section 302 Extremely Hazardous Substances (40 CFR 355):**

None.

**Section 304 CERCLA Hazardous Substances (40 CFR 302):**

None.

**Section 311/312 Hazard Class (40 CFR 370):**

Acute: No  
Chronic: No  
Fire: No  
Pressure: No  
Reactive: No

**Section 313 Toxic Chemicals (40 CFR 372):**

None present or none present in regulated quantities.

Note: Chemicals are listed under the 313 Toxic Chemicals section only if they meet or exceed a reporting threshold.

**Supplemental State Compliance Information**

**MOLYKOTE(R) 33 LIGHT EXTREME LOW TEMPERATURE GREASE****California**

Warning: This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm.

None known.

**Massachusetts**

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
4485-12-5	15.0 - 40.0	Lithium stearate

**New Jersey**

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
63148-52-7	> 60.0	Dimethyl, phenylmethyl siloxane, trimethyl-terminated
4485-12-5	15.0 - 40.0	Lithium stearate

**Pennsylvania**

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
63148-52-7	> 60.0	Dimethyl, phenylmethyl siloxane, trimethyl-terminated
4485-12-5	15.0 - 40.0	Lithium stearate

**16. OTHER INFORMATION**

Prepared by: Dow Corning Corporation

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

(R) indicates Registered Trademark