

MATERIAL SAFETY DATA SHEET

PR-1422 A-2, Part A  
FM3101A

Effective Date: 10/30/2000

SECTION I - MANUFACTURER AND PRODUCT INFORMATION

PRC-DeSoto International, Inc.  
A PPG Industries Company  
5430 San Fernando Road  
P.O. Box 1800  
Glendale, CA 91209

Information Phone: (818) 240-2060  
Emergency Phone: (800) 228-5635  
CHEMTREC: (800) 424-9300

Trade Name: PR-1422 A-2, Part A  
Accelerator component  
Product Code: FM3101A  
Form ID No: A04  
Product Class: Inorganic dichromate solution  
Synonyms: S-3101

HMIS HAZARD RATING  
HEALTH - 3  
FLAMMABILITY - 1  
REACTIVITY - 0  
PPE - G  
None (0) --->Extreme (4)

SECTION II - COMPOSITION

INGREDIENTS INFORMATION

CAS NUMBER	Wt %	CHEMICAL IDENTITY
000127-19-5	30 - 60	Dimethylacetamide
014307-33-6	10 - 30	Calcium dichromate
001332-58-7	1 - 10	Kaolin
001333-86-4	< 2	Carbon Black

EXPOSURE LIMITS

CAS NUMBER	EXPOSURE LIMITS (ppm)				
	ACGIH TLVs		OSHA PELs		
	TWA	STEL	TWA	STEL	
000127-19-5	10	N/E	10	N/E	S
014307-33-6	0.05 mg/M3N/E		0.05 mg/M3N/E		
001332-58-7	2 mg/m3	N/E	10 mg/m3	N/E	S
001333-86-4	3.5 mg/m3	N/E	3.5 mg/m3	N/E	S

Footnotes

(S) Occupational Exposure Standard  
(R) Supplier's Recommended Limit

N/Av = Not Available

N.E. = Not Established

N/Ap = Not Applicable

NotknownXXX = CAS Number is not known.

MATERIAL SAFETY DATA SHEET

PR-1422 A-2, Part A  
FM3101A

Effective Date: 10/30/2000

SECTION III - HAZARDS IDENTIFICATION

Permissible Exposure Limits for Product:  
Not established for product. See Section II.

ROUTE OF ENTRY AND EFFECTS OF OVEREXPOSURE

ROUTE OF ENTRY:

Inhalation and dermal.

INHALATION:

Vapor will irritate nose, throat and respiratory tract. High vapor concentration may cause dizziness, drowsiness and fatigue.

EYE CONTACT:

Vapor or substance is severely irritating to eyes and cause redness and tearing.

SKIN CONTACT:

Substance can cause severe skin irritation with drying, defatting, splitting and cracking on repeated contact.

INGESTION:

Substance can cause irritation of gastro-intestinal tract followed by nausea, vomiting and abdominal discomfort.

DELAYED EFFECTS:

Repeated overexposure may cause kidney/liver damage.

Contains an ingredient listed as known or suspected carcinogen?

NTP: Yes

OSHA: No

IARC: Yes

SECTION IV - FIRST AID MEASURES

INHALATION:

If inhaled, remove from area to fresh air. If not breathing, give artificial respiration. Get immediate medical attention. If breathing is difficult, transport to medical facility and, if available, give supplemental oxygen.

EYE CONTACT:

For eye contact, immediately flush eyes for at least 15 minutes with running water. Hold eyelids apart to ensure rinsing of the entire eye surface and lids with water. Get immediate medical attention.

SKIN CONTACT:

For skin contact, wipe excess material with dry towel. Then wash exposed areas with plenty of water, and soap if available, for several minutes. Get medical attention if irritation occurs.

MATERIAL SAFETY DATA SHEET

PR-1422 A-2, Part A  
FM3101A

Effective Date: 10/30/2000

INGESTION:

If swallowed dilute by giving two(2) glasses of water to drink. Get immediate medical attention. Never give anything by mouth to an unconscious person.

GENERAL:

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

SECTION V - FIRE AND EXPLOSION HAZARD IDENTIFICATION

FLASHPOINT: N/Av

Method: Not Applicable

LEL (%): N/Av

UEL (%): N/Av

FLAMMABILITY CLASSIFICATION:

Not flammable.

FIRE AND EXPLOSION HAZARDS:

Decomposition and combustion products may be hazardous. No unusual hazards known.

EXTINGUISHING MEDIA:

Carbon dioxide, dry chemical, foam, water fog.

FIRE FIGHTING PROCEDURES:

Use complete personal protection. Use water to cool heat exposed containers.

SECTION VI - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Dike and cover spill with non-oxidizable absorbent. Scoop into containers. Sprinkle sodium thiosulfate on the residue and work in. Scoop into disposal container. Clean up with water. Wear appropriate personal protective equipment (See Section VIII).

PR-1422 A-2, Part A  
FM3101A

MATERIAL SAFETY DATA SHEET

Effective Date: 10/30/2000

SECTION VII - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Keep container tightly closed. Store in a dry location. Wear proper personal protective equipment (See Section VIII). Wash thoroughly after handling and before smoking or eating.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS:

Good general mechanical ventilation.

RESPIRATORY PROTECTION:

Not normally required.

EYE PROTECTION:

Safety glasses.

SKIN PROTECTION:

Chemically resistant gloves.

GENERAL:

Safety shower, eye wash station and washing facilities should be available. When using in circumstances where skin contact is likely, use complete protective garments.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Black
Physical State:	Paste
Low Boiling Point:	212 F 99.99 C
High Boiling Point:	331 F 166.09 C
Evaporation Rate:	Slower than n-butyl acetate
Vapor Density:	Heavier than air
% Volatiles by Volume:	75.9
Specific Gravity:	1.393
Liquid Density:	Heavier than water
Weight Per Gallon:	11.6
VOC (GR/L):	N/Av
VOC (GR/L, Combined):	N/Av

MATERIAL SAFETY DATA SHEET

PR-1422 A-2, Part A  
FM3101A

Effective Date: 10/30/2000

SECTION X - STABILITY AND REACTIVITY

STABILITY:

Stable.

HAZARDOUS POLYMERIZATION:

Will not occur.

INCOMPATIBILITY:

Strong oxidizing agents, strong acids.

CONDITIONS TO AVOID:

See incompatibilities above.

HAZARDOUS DECOMPOSITION PRODUCTS:

Oxides of carbon and nitrogen, chromium compounds.

SECTION XI - TOXICOLOGICAL INFORMATION

ACUTE ORAL, DERMAL AND INHALATION EFFECTS (LD50 AND LC50):

CAS NUMBER	LD50	LC50
000127-19-5	5680 mg/kg, oral, rat	N/AV.
014307-33-6	5000 mg/kg	N/Av
001332-58-7	N/AV.	N/AV.
001333-86-4	440 mg/kg, oral, rat	6750 mg/m3, rat, 4hr.

Carcinogenicity:

Carbon Black:

Based on an IARC conclusion that there is "sufficient evidence in experimental animals for the carcinogenicity of carbon black" and inadequate evidence of carcinogenicity in humans. IARC's overall evaluation is that "carbon black is possibly carcinogenic to humans" (Group 2B).

Carbon black has not been listed as a carcinogen by National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety & Health (NIOSH) criteria document on carbon black recommends that only carbon blacks with PAH levels greater than 0.1% be considered suspect carcinogens.

Chromium Compounds (Calcium dichromate):

MATERIAL SAFETY DATA SHEET

PR-1422 A-2, Part A  
FM3101A

Effective Date: 10/30/2000

NTP and IARC have determined that there is sufficient evidence for the carcinogenicity of hexavalent chromium compounds both in humans and experimental animals.

Prolonged or repeated eye contact may cause conjunctivitis.  
Prolonged or repeated skin contact, especially with broken skin, may cause "chrome sores". Prolonged or repeated inhalation of mist or fume may cause ulceration and perforation of nasal septum.  
Prolonged inhalation may cause liver damage.

NOTICE:

There are no data available on the product itself.

SECTION XII - ECOLOGICAL INFORMATION

NOTICE:

There are no data available on the product itself.

SECTION XIII - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD:

When disposing of this material, ensure that it is packaged, stored, transported, and otherwise handled in accordance with local, state, and federal regulations.

EPA WASTE NUMBERS:

D-007 (Chromium)

SECTION XIV - TRANSPORT INFORMATION

DOT (Non-Bulk):

PROPER SHIPPING NAME: Not regulated  
HAZARD CLASS: Not Applicable  
UN NUMBER: Not Available

SPECIAL NOTES:

None

MATERIAL SAFETY DATA SHEET

PR-1422 A-2, Part A  
FM3101A

Effective Date: 10/30/2000

SECTION XV - REGULATORY INFORMATION

TSCA Section 8(b) - Inventory Status:

All ingredients in this product are listed in the TSCA Inventory or are exempt from listing.

CANADIAN EPA - DSL Inventory Status:

The DSL status of this product is unknown at this time.

SARA Title III Section 313 - Toxic Chemical List (TCL):

This product contains a toxic chemical for routine annual "Toxic Chemical Release Reporting" under Section 313 (40 CFR 372). This information must be included in all MSDS's copied or distributed for this product.

014307-33-6 Calcium dichromate

SARA Title III Section 302 - CERCLA:

This product contains the following chemicals regulated under Section 302 as extremely hazardous substance(s) for emergency release notification (CERCLA List).

014307-33-6 Calcium dichromate

1

CALIFORNIA PROPOSITION 65 - Reportable ingredients:

Chemicals known by the state of CA to cause cancer:

This product contains the following chemical which is known to the state of California to cause cancer.

014307-33-6 Calcium dichromate

Chemicals known by the state of CA to cause reproductive toxicity:

This product does not contain any chemicals currently on the California list of known Reproductive Toxins.

TSCA Section 12(b) - Export Notification:

This product does not contain any chemicals subject to Section 12(b) export notification.

MATERIAL SAFETY DATA SHEET

PR-1422 A-2, Part A  
FM3101A

Effective Date: 10/30/2000

CLEAN AIR ACT - Hazardous Air Pollutants (CAA Section 112):

This product contains the following chemicals regulated under Section 112 for National Emission Standards of Hazardous Air Pollutants notification.

014307-33-6 Calcium dichromate

Pennsylvania Right to Know - Reportable Ingredients:

The following is required composition information. Also, review Section II for additional information for other chemicals.

000127-19-5 Dimethylacetamide  
001332-58-7 Kaolin  
001333-86-4 Carbon Black  
014307-33-6 Calcium dichromate

New Jersey Right to Know - Reportable Ingredients:

The following is required composition information. Also, review Section II for additional information for other chemicals.

000127-19-5 Dimethylacetamide  
001333-86-4 Carbon Black

SECTION XVI - OTHER INFORMATION

Effective Date: 10/30/2000 Supersedes Date: 12/19/1996  
Revision Number: 01

The information in this MSDS was obtained from sources which we believe to be reliable. However, since much of the information has been received from sources outside the company, it is provided without any warranty, expressed or implied, regarding its correctness, or suitability for specific situations. The conditions of handling, storage, use, and disposal of this product are beyond our control and may be beyond our knowledge. The user has the sole responsibility to determine the suitability of the material for any use, and the manner and conditions of use. Therefore, we cannot assume responsibility and expressly disclaim liability for loss, damage, injury, or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. Effects can be aggravated by other materials and/or this material may

MATERIAL SAFETY DATA SHEET

PR-1422 A-2, Part A  
FM3101A

Effective Date: 10/30/2000

aggravate or add to the effects of other materials.

End of Document

MATERIAL SAFETY DATA SHEET

PR-1422 A-2, Part B  
FM0869

Effective Date: 05/15/01

SECTION I - MANUFACTURER AND PRODUCT INFORMATION

PRC-DeSoto International, Inc.  
A PPG Industries Company  
5430 San Fernando Road  
P.O. Box 1800  
Glendale, CA 91209

Information Phone: (818) 240-2060  
Emergency Phone: (800) 228-5635  
CHEMTREC: (800) 424-9300

Trade Name: PR-1422 A-2, Part B  
Base component

Product Code: FM0869

Form ID No: B04

Product Class: Filled Modified polysulfide resin

Synonyms: P-0869

HMIS HAZARD RATING

HEALTH - 2

FLAMMABILITY - 3

REACTIVITY - 0

PPE - H

None (0) --->Extreme (4)

SECTION II - COMPOSITION

INGREDIENTS INFORMATION

CAS NUMBER	Wt %	CHEMICAL IDENTITY
068611-50-7	60 - 90	Liquid Polysulphide Polymer with Thiol End Groups
000078-93-3	1 - 10	Methyl Ethyl Ketone
028470-78-2	< 5	Formaldehyde polymer w/ 3-Chloro-1-Propene & Phenol
025036-25-3	< 5	Bisphenol A/Epichlorohydrin Based Epoxy Resin
000108-88-3	< 5	Toluene

EXPOSURE LIMITS

CAS NUMBER	EXPOSURE LIMITS (ppm)				
	ACGIH TLVs		OSHA PELs		
	TWA	STEL	TWA	STEL	
068611-50-7	N/E	N/E	N/E	N/E	
000078-93-3	200	300	200	300	S
028470-78-2	N/E	N/E	N/E	N/E	
025036-25-3	10 mg/m3	N/E	15 mg/m3	N/E	S
000108-88-3	50	N/E	100	N/E	S

Footnotes

(S) Occupational Exposure Standard  
(R) Supplier's Recommended Limit

MATERIAL SAFETY DATA SHEET

PR-1422 A-2, Part B  
FM0869

Effective Date: 05/15/01

N/Av = Not Available

N/Ap = Not Applicable

N.E. = Not Established

NotknownXXX = CAS Number is not known.

SECTION III - HAZARDS IDENTIFICATION

Permissible Exposure Limits for Product:

Not established for product. See Section II.

ROUTE OF ENTRY AND EFFECTS OF OVEREXPOSURE

ROUTE OF ENTRY:

Inhalation and dermal.

INHALATION:

Vapor and mist will irritate nose, throat and respiratory tract.  
High vapor concentration may cause dizziness, drowsiness and fatigue.

EYE CONTACT:

Vapor, mist or liquid is severely irritating to eyes and cause blurred vision, redness and tearing.

SKIN CONTACT:

Liquid can cause severe skin irritation with drying, defatting, splitting and cracking on repeated contact.

INGESTION:

Liquid can cause irritation of gastro-intestinal tract followed by nausea and vomiting, abdominal discomfort, and rapid pulse.

DELAYED EFFECTS:

Repeated overexposure may cause headaches, dizziness, drowsiness, unconsciousness and central nervous system effects.

Contains an ingredient listed as known or suspected carcinogen?

NTP: No

OSHA: No

IARC: No

SECTION IV - FIRST AID MEASURES

INHALATION:

If inhaled, remove from area to fresh air. If not breathing, give artificial respiration. Get immediate medical attention. If breathing is difficult, transport to medical facility and, if available, give supplemental oxygen.

EYE CONTACT:

For eye contact, immediately flush eyes for at least 15 minutes with running water. Hold eyelids apart to ensure rinsing of the

MATERIAL SAFETY DATA SHEET

PR-1422 A-2, Part B  
FM0869

Effective Date: 05/15/01

entire eye surface and lids with water. Get immediate medical attention.

SKIN CONTACT:

For skin contact, wipe excess material with dry towel. Then wash exposed areas with plenty of water, and soap if available, for several minutes. Get medical attention if irritation occurs.

INGESTION:

If swallowed dilute by giving two(2) glasses of water to drink. Get immediate medical attention. Never give anything by mouth to an unconscious person.

GENERAL:

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

SECTION V - FIRE AND EXPLOSION HAZARD IDENTIFICATION

FLASHPOINT: 59 F 15 C

Method: PMCC

LEL (%): 1.3

UEL (%): N/AV

FLAMMABILITY CLASSIFICATION:

Flammable

FIRE AND EXPLOSION HAZARDS:

Decomposition and combustion products may be hazardous. High temperatures may cause pressure build-up in closed containers. Vapors may accumulate in inadequately ventilated or confined areas. Vapors may form explosive mixture with air. Vapors are heavier than air and may travel long distances. Flashback or flame to the handling site may occur. Closed containers may explode when exposed to extreme heat.

EXTINGUISHING MEDIA:

Carbon dioxide, dry chemical, foam.

FIRE FIGHTING PROCEDURES:

Water spray may be ineffective. Cool fire exposed containers with water. Fog nozzles are preferable. Wear NIOSH/MSHA approved self-contained breathing apparatus and complete protective clothing to prevent contact with skin and eyes.

MATERIAL SAFETY DATA SHEET

PR-1422 A-2, Part B  
FM0869

Effective Date: 05/15/01

SECTION VI - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Remove all ignition sources. Wear an air-supplied respirator for an unventilated spill. Cover with absorbent. Scoop into containers using non-sparking tools. Clean up residue with a suitable cleaning solvent. Wear appropriate personal protective equipment (See Section VIII).

SECTION VII - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Keep container tightly closed. Isolate from heat, electrical equipment, sparks and flame. Use grounding and bonding procedures during transfer. Do not store above 120 degrees F. Vapors of this product are heavier than air and may collect in low or confined areas. Empty drums may contain explosive vapors. Do not cut, puncture, or weld on or near drum. Wear proper personal protective equipment (See Section VIII). Wash thoroughly after handling and before smoking or eating.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS:

Local and/or general ventilation as required to maintain hazardous ingredients below recommended (ACGIH-TLV) or regulated (OSHA-PEL) limits.

RESPIRATORY PROTECTION:

When spraying or applying in any circumstances likely to produce airborne levels of solvent vapors in excess of the TLV, use an organic vapor cartridge or air-supplied respirator.

EYE PROTECTION:

Chemical goggles or full-face shield.

SKIN PROTECTION:

Solvent resistant gloves.

GENERAL:

Safety shower, eye wash station and washing facilities should be available. When using in circumstances where skin contact is likely, use complete protective garments.



PR-1422 A-2, Part B  
FM0869

MATERIAL SAFETY DATA SHEET

Effective Date: 05/15/01

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Brown
Physical State:	Viscous liquid
Low Boiling Point:	N/Av
High Boiling Point:	N/Av
Evaporation Rate:	Slower than n-butyl acetate
Vapor Density:	Heavier than air
% Volatiles by Volume:	18
Specific Gravity:	1.361
Liquid Density:	Heavier than water
Weight Per Gallon:	11.34
VOC (GR/L):	N/Av
VOC (GR/L, Combined):	192

SECTION X - STABILITY AND REACTIVITY

STABILITY:

Stable.

HAZARDOUS POLYMERIZATION:

Will not occur.

INCOMPATIBILITY:

Strong oxidizing agents.

CONDITIONS TO AVOID:

See incompatibilities above.

HAZARDOUS DECOMPOSITION PRODUCTS:

Oxides of carbon and nitrogen, sulfur dioxide, traces of hydrogen sulfide.

PR-1422 A-2, Part B  
FM0869

MATERIAL SAFETY DATA SHEET

Effective Date: 05/15/01

SECTION XI - TOXICOLOGICAL INFORMATION

ACUTE ORAL, DERMAL AND INHALATION EFFECTS (LD50 AND LC50):

CAS NUMBER	LD50	LC50
068611-50-7	5000 mg/kg, oral, rat	N/AV.
000078-93-3	2740 mg/kg, oral, rat	11700 ppm, rat, 4hr.
028470-78-2	N/AV.	N/AV.
025036-25-3	3000 mg/kg, oral, rat	800 mg/m3, rat, 4hr.
000108-88-3	2600 mg/kg, oral, rat	8800 ppm, rat, 4hr.

NOTICE:

There are no data available on the product itself.

SECTION XII - ECOLOGICAL INFORMATION

NOTICE:

There are no data available on the product itself.

SECTION XIII - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD:

When disposing of this material, ensure that it is packaged, stored, transported, and otherwise handled in accordance with local, state, and federal regulations.

EPA WASTE NUMBERS:

D-001 (Ignitable)

SECTION XIV - TRANSPORT INFORMATION

DOT (Non-Bulk):

PROPER SHIPPING NAME:	Adhesives
HAZARD CLASS:	3
UN NUMBER:	UN 1133
PACKING GROUP:	II
LABEL:	Flammable liquid

MATERIAL SAFETY DATA SHEET

PR-1422 A-2, Part B  
FM0869

Effective Date: 05/15/01

SPECIAL NOTES:

If package size is < 6.6 gallons, then Packing Group III according to 49 CFR 173.121(b) and IATA 3.3.3.

SECTION XV - REGULATORY INFORMATION

TSCA Section 8(b) - Inventory Status:

All ingredients in this product are listed in the TSCA Inventory or are exempt from listing.

CANADIAN EPA - DSL Inventory Status:

The DSL status of this product is unknown at this time.

SARA Title III Section 313 - Toxic Chemical List (TCL):

This product contains a toxic chemical for routine annual "Toxic Chemical Release Reporting" under Section 313 (40 CFR 372). This information must be included in all MSDS's copied or distributed for this product.

000078-93-3 Methyl Ethyl Ketone  
000108-88-3 Toluene

SARA Title III Section 302 - CERCLA:

This product contains the following chemicals regulated under Section 302 as extremely hazardous substance(s) for emergency release notification (CERCLA List).

000078-93-3 Methyl Ethyl Ketone 5000  
000108-88-3 Toluene 1000

CALIFORNIA PROPOSITION 65 - Reportable ingredients:

Chemicals known by the state of CA to cause cancer:

This product contains the following chemical which is known to the state of California to cause cancer.

000050-00-0 Formaldehyde  
014808-60-7 Crystalline Silica Quartz

Chemicals known by the state of CA to cause reproductive toxicity:

This product contains the following chemical which is known to the state of California to cause reproductive toxicity.

MATERIAL SAFETY DATA SHEET

PR-1422 A-2, Part B  
EM0869

Effective Date: 05/15/01

000108-88-3 Toluene

TSCA Section 12(b) - Export Notification:

This product contains following chemical that required annual or one time export notification per chemical and per country.

000108-95-2 Phenol

CLEAN AIR ACT - Hazardous Air Pollutants (CAA Section 112):

This product contains the following chemicals regulated under Section 112 for National Emission Standards of Hazardous Air Pollutants notification.

000050-00-0 Formaldehyde  
000078-93-3 Methyl Ethyl Ketone  
000108-88-3 Toluene  
000108-95-2 Phenol

Pennsylvania Right to Know - Reportable Ingredients:

The following is required composition information. Also, review Section II for additional information for other chemicals.

000050-00-0 Formaldehyde  
000078-93-3 Methyl Ethyl Ketone  
000108-88-3 Toluene  
001309-37-1 Red Iron Oxide  
001333-86-4 Carbon Black

New Jersey Right to Know - Reportable Ingredients:

The following is required composition information. Also, review Section II for additional information for other chemicals.

000078-93-3 Methyl Ethyl Ketone  
000108-88-3 Toluene

---

MATERIAL SAFETY DATA SHEET

PR-1422 A-2, Part B  
FM0869

Effective Date: 05/15/01

---

SECTION XVI - OTHER INFORMATION

---

Effective Date: 05/15/01      Supersedes Date: 12/01/2000  
Revision Number: 02  
Revision Reason: Revised Section 14

The information in this MSDS was obtained from sources which we believe to be reliable. However, since much of the information has been received from sources outside the company, it is provided without any warranty, expressed or implied, regarding its correctness, or suitability for specific situations. The conditions of handling, storage, use, and disposal of this product are beyond our control and may be beyond our knowledge. The user has the sole responsibility to determine the suitability of the material for any use, and the manner and conditions of use. Therefore, we cannot assume responsibility and expressly disclaim liability for loss, damage, injury, or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. Effects can be aggravated by other materials and/or this material may aggravate or add to the effects of other materials.

---

End of Document

