

MATERIAL SAFETY DATA SHEET

PR-2050 B-1/2, Part A  
FM5419A

Effective Date: 06/20/01

SECTION I - MANUFACTURER AND PRODUCT INFORMATION

PRC-DeSoto International, Inc.  
A PPG Industries Company  
5430 San Fernando Road  
P.O. Box 1800  
Glendale, CA 91209

Information Phone: (818) 240-2060  
Emergency Phone: (800) 228-5635  
CHEMTREC: (800) 424-9300

Trade Name: PR-2050 B-1/2, Part A  
Accelerator component  
Product Code: FM5419A  
Form ID No: X01  
Product Class: Filled epoxy resins mixture  
Synonyms: S-5419

HMIS HAZARD RATING  
HEALTH - 2  
FLAMMABILITY - 2  
REACTIVITY - 0  
PPE - G  
None (0)--->Extreme (4)

SECTION II - COMPOSITION

INGREDIENTS INFORMATION

CAS NUMBER	Wt %	CHEMICAL IDENTITY
028064-14-4	30 - 60	Polymer of Epichlorohydrin, Phenol-Formaldehyde Nov
061788-32-7	10 - 30	Hydrogenated Terphenyl
000078-93-3	1 - 10	Methyl Ethyl Ketone
002530-83-8	< 5	Gamma-Glycidoxypropyltrimeth- oxysilane
026140-60-3	< 5	Terphenyls
000057-11-4	< 5	Stearic Acid
001333-86-4	< 2	Carbon Black

EXPOSURE LIMITS

CAS NUMBER	EXPOSURE LIMITS (ppm)				
	ACGIH TLVs		OSHA PELs		
	TWA	STEL	TWA	STEL	
028064-14-4	N/E	N/E	N/E	N/E	
061788-32-7	0.5	N/E	0.5	N/E	S
000078-93-3	200	300	200	300	S
002530-83-8	N/E	N/E	N/E	N/E	
026140-60-3	0.5	N/E	0.5	N/E	S
000057-11-4	N/E	N/E	N/E	N/E	
001333-86-4	3.5 mg/m3	N/E	3.5 mg/m3	N/E	S

-----  
MATERIAL SAFETY DATA SHEET

PR-2050 B-1/2, Part A  
FM5419A

Effective Date: 06/20/01  
-----

Footnotes

- (S) Occupational Exposure Standard
- (R) Supplier's Recommended Limit

N/Av = Not Available

N/Ap = Not Applicable

N.E. = Not Established

NotknownXXX = CAS Number is not known.  
-----

SECTION III - HAZARDS IDENTIFICATION  
-----

Permissible Exposure Limits for Product:

Not established for product. See Section II.

ROUTE OF ENTRY AND EFFECTS OF OVEREXPOSURE

ROUTE OF ENTRY:

Inhalation and dermal.

INHALATION:

Vapor or fume will irritate the nose and throat.

EYE CONTACT:

Vapor or fume can irritate the eyes.

SKIN CONTACT:

Substance can cause moderate irritation.

INGESTION:

Ingestion can cause irritation of gastro-intestinal tract.

DELAYED EFFECTS:

Repeated overexposure may cause headaches, dizziness, drowsiness, unconsciousness and central nervous system effects.

Contains an ingredient listed as known or suspected carcinogen?

NTP: No

OSHA: No

IARC: Yes  
-----

SECTION IV - FIRST AID MEASURES  
-----

INHALATION:

If inhaled, remove from area to fresh air. If not breathing, give artificial respiration. Get immediate medical attention. If breathing is difficult, transport to medical facility and, if available, give supplemental oxygen.

EYE CONTACT:

For eye contact, immediately flush eyes for at least 15 minutes with running water. Hold eyelids apart to ensure rinsing of the entire eye surface and lids with water. Get immediate medical  
-----

-----  
MATERIAL SAFETY DATA SHEET

PR-2050 B-1/2, Part A  
FM5419A

Effective Date: 06/20/01  
-----

attention.

SKIN CONTACT:

For skin contact, wipe excess material with dry towel. Then wash exposed areas with plenty of water, and soap if available, for several minutes. Get medical attention if irritation occurs.

INGESTION:

If swallowed dilute by giving two(2) glasses of water to drink. Get immediate medical attention. Never give anything by mouth to an unconscious person.

GENERAL:

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.  
-----

SECTION V - FIRE AND EXPLOSION HAZARD IDENTIFICATION  
-----

FLASHPOINT: 130 F 54.44 C Method: Setaflash  
LEL (%): N/Av UEL (%): N/Av

FLAMMABILITY CLASSIFICATION:

Flammable

FIRE AND EXPLOSION HAZARDS:

Decomposition and combustion products may be hazardous. High temperatures may cause pressure build-up in closed containers. Vapors may accumulate in inadequately ventilated or confined areas. Vapors may form explosive mixture with air. Vapors are heavier than air and may travel long distances. Flashback or flame to the handling site may occur. Closed containers may explode when exposed to extreme heat.

EXTINGUISHING MEDIA:

Carbon dioxide, dry chemical, foam.

FIRE FIGHTING PROCEDURES:

Water spray may be ineffective. Cool fire exposed containers with water. Fog nozzles are preferable. Wear NIOSH/MSHA approved self-contained breathing apparatus and complete protective clothing to prevent contact with skin and eyes.  
-----

-----  
MATERIAL SAFETY DATA SHEET

PR-2050 B-1/2, Part A  
FM5419A

Effective Date: 06/20/01  
-----

SECTION VI - ACCIDENTAL RELEASE MEASURES  
-----

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Remove all ignition sources. Wear an air-supplied respirator for an unventilated spill. Cover with absorbent. Scoop into containers using non-sparking tools. Clean up residue with a suitable cleaning solvent. Wear appropriate personal protective equipment (See Section VIII).  
-----

SECTION VII - HANDLING AND STORAGE  
-----

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Keep container tightly closed. Store in a dry location. Wear proper personal protective equipment (See Section VIII). Wash thoroughly after handling and before smoking or eating.  
-----

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION  
-----

ENGINEERING CONTROLS:

Local and/or general ventilation as required to maintain hazardous ingredients below recommended (ACGIH-TLV) or regulated (OSHA-PEL) limits.

RESPIRATORY PROTECTION:

When spraying or applying in any circumstances likely to produce airborne levels of solvent vapors in excess of the TLV, use an organic vapor cartridge or air-supplied respirator.

EYE PROTECTION:

Chemical goggles or full-face shield.

SKIN PROTECTION:

Solvent resistant gloves.

GENERAL:

Safety shower, eye wash station and washing facilities should be available. When using in circumstances where skin contact is likely, use complete protective garments.  
-----

-----  
MATERIAL SAFETY DATA SHEET

PR-2050 B-1/2, Part A  
FM5419A

Effective Date: 06/20/01  
-----

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES  
-----

Appearance: Black  
Physical State: Paste  
Low Boiling Point: N/Av  
High Boiling Point: N/Av  
Evaporation Rate: Non-volatile  
Vapor Density: Heavier than air  
% Volatiles by Volume: 9  
Specific Gravity: 1.40  
Liquid Density: Heavier than water  
Weight Per Gallon: 11.65  
VOC (GR/L): N/Av  
VOC (GR/L, Combined): N/Av  
-----

SECTION X - STABILITY AND REACTIVITY  
-----

STABILITY:

Stable.

HAZARDOUS POLYMERIZATION:

Will not occur.

INCOMPATIBILITY:

Strong oxidizing agents, strong acids.

CONDITIONS TO AVOID:

See incompatibilities above.

HAZARDOUS DECOMPOSITION PRODUCTS:

Products of combustion are hazardous including carbon monoxide,  
carbon dioxide, and oxides of nitrogen.  
-----

SECTION XI - TOXICOLOGICAL INFORMATION  
-----

-----  
MATERIAL SAFETY DATA SHEET

PR-2050 B-1/2, Part A  
FM5419A

Effective Date: 06/20/01  
-----

ACUTE ORAL, DERMAL AND INHALATION EFFECTS (LD50 AND LC50):

CAS NUMBER	LD50	LC50
028064-14-4	4000 mg/kg, oral, rat	N/AV.
061788-32-7	10000 mg/kg, oral, rat	4.7 mg/L, rat, 4hr.
000078-93-3	2740 mg/kg, oral, rat	11700 ppm, rat, 4hr.
002530-83-8	23000 mg/kg, oral, rat	N/AV.
026140-60-3	10000 mg/kg, oral, rat	4.7 mg/L, rat, 4hr.
000057-11-4	5000 mg/kg, oral, rat	N/AV.
001333-86-4	440 mg/kg, oral, rat	6750 mg/m3, rat, 4hr.

-----

Carcinogenicity:

Carbon Black:

Based on an IARC conclusion that there is "sufficient evidence in experimental animals for the carcinogenicity of carbon black" and inadequate evidence of carcinogenicity in humans. IARC's overall evaluation is that "carbon black is possibly carcinogenic to humans" (Group 2B).

Carbon black has not been listed as a carcinogen by National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety & Health (NIOSH) criteria document on carbon black recommends that only carbon blacks with PAH levels greater than 0.1% be considered suspect carcinogens.

NOTICE:

There are no data available on the product itself.  
-----

SECTION XII - ECOLOGICAL INFORMATION  
-----

NOTICE:

There are no data available on the product itself.  
-----

-----  
MATERIAL SAFETY DATA SHEET

PR-2050 B-1/2, Part A  
FM5419A

Effective Date: 06/20/01  
-----

SECTION XIII - DISPOSAL CONSIDERATIONS  
-----

WASTE DISPOSAL METHOD:

When disposing of this material, ensure that it is packaged, stored, transported, and otherwise handled in accordance with local, state, and federal regulations.

EPA WASTE NUMBERS:

D-001 (Ignitable)  
-----

SECTION XIV - TRANSPORT INFORMATION  
-----

DOT (Non-Bulk):

PROPER SHIPPING NAME: Adhesives  
HAZARD CLASS: 3  
UN NUMBER: UN 1133  
PACKING GROUP: III  
LABEL: Flammable liquid

SPECIAL NOTES:

None  
-----

SECTION XV - REGULATORY INFORMATION  
-----

TSCA Section 8(b) - Inventory Status:

All ingredients in this product are listed in the TSCA Inventory or are exempt from listing.

CANADIAN EPA - DSL Inventory Status:

The DSL status of this product is unknown at this time.

SARA Title III Section 313 - Toxic Chemical List (TCL):

This product contains a toxic chemical for routine annual "Toxic Chemical Release Reporting" under Section 313 (40 CFR 372). This information must be included in all MSDS's copied or distributed for this product.

000078-93-3 Methyl Ethyl Ketone  
-----

-----  
MATERIAL SAFETY DATA SHEET

PR-2050 B-1/2, Part A  
FM5419A

Effective Date: 06/20/01  
-----

SARA Title III Section 302 - CERCLA:

This product contains the following chemicals regulated under Section 302 as extremely hazardous substance(s) for emergency release notification (CERCLA List).

000078-93-3 Methyl Ethyl Ketone 5000

CALIFORNIA PROPOSITION 65 - Reportable ingredients:

Chemicals known by the state of CA to cause cancer:

This product does not contain any chemicals currently on the California list of known carcinogens.

Chemicals known by the state of CA to cause reproductive toxicity:

This product does not contain any chemicals currently on the California list of known Reproductive Toxins.

TSCA Section 12(b) - Export Notification:

This product does not contain any chemicals subject to Section 12(b) export notification.

CLEAN AIR ACT - Hazardous Air Pollutants (CAA Section 112):

This product contains the following chemicals regulated under Section 112 for National Emission Standards of Hazardous Air Pollutants notification.

000067-56-1 Methyl Alcohol  
000078-93-3 Methyl Ethyl Ketone

Pennsylvania Right to Know - Reportable Ingredients:

The following is required composition information. Also, review Section II for additional information for other chemicals.

000078-93-3 Methyl Ethyl Ketone  
001333-86-4 Carbon Black  
026140-60-3 Terphenyls  
061788-32-7 Hydrogenated Terphenyl

New Jersey Right to Know - Reportable Ingredients:

The following is required composition information. Also, review Section II for additional information for other chemicals.



-----  
MATERIAL SAFETY DATA SHEET

PR-2050 B-1/2, Part A  
FM5419A

Effective Date: 06/20/01  
-----

000078-93-3      Methyl Ethyl Ketone  
001333-86-4      Carbon Black  
-----

SECTION XVI - OTHER INFORMATION  
-----

Effective Date: 06/20/01      Supersedes Date: 06/20/2001  
Revision Number: 00  
Revision Reason: New Product

The information in this MSDS was obtained from sources which we believe to be reliable. However, since much of the information has been received from sources outside the company, it is provided without any warranty, expressed or implied, regarding its correctness, or suitability for specific situations. The conditions of handling, storage, use, and disposal of this product are beyond our control and may be beyond our knowledge. The user has the sole responsibility to determine the suitability of the material for any use, and the manner and conditions of use. Therefore, we cannot assume responsibility and expressly disclaim liability for loss, damage, injury, or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. Effects can be aggravated by other materials and/or this material may aggravate or add to the effects of other materials.

-----

End of Document

MATERIAL SAFETY DATA SHEET

PR-2050 B-1/2, Part B  
FM5456

Effective Date: 06/20/01

SECTION I - MANUFACTURER AND PRODUCT INFORMATION

PRC-DeSoto International, Inc.  
A PPG Industries Company  
5430 San Fernando Road  
P.O. Box 1800  
Glendale, CA 91209

Information Phone: (818) 240-2060  
Emergency Phone: (800) 228-5635  
CHEMTREC: (800) 424-9300

Trade Name: PR-2050 B-1/2, Part B  
Base component  
Product Code: FM5456  
Form ID No: X01  
Product Class: Filled polythioether  
Synonyms: P-5456

HMIS HAZARD RATING  
HEALTH - 2  
FLAMMABILITY - 2  
REACTIVITY - 0  
PPE - H  
None (0) --->Extreme (4)

SECTION II - COMPOSITION

INGREDIENTS INFORMATION

CAS NUMBER	Wt %	CHEMICAL IDENTITY
REF00000005	30 - 60	Thiol terminated polythioetherpolyether
001330-20-7	< 5	Xylene
061788-32-7	< 5	Hydrogenated Terphenyl

EXPOSURE LIMITS

CAS NUMBER	EXPOSURE LIMITS (ppm)				S
	ACGIH TLVs		OSHA PELs		
	TWA	STEL	TWA	STEL	
REF00000005	N/E	N/E	N/E	N/E	
001330-20-7	100	150	100	150	S
061788-32-7	0.5	N/E	0.5	N/E	S

Footnotes

(S) Occupational Exposure Standard  
(R) Supplier's Recommended Limit

N/Av = Not Available  
N.E. = Not Established  
N/Ap = Not Applicable  
NotknownXXX = CAS Number is not known.

-----  
MATERIAL SAFETY DATA SHEET

PR-2050 B-1/2, Part B  
FM5456

Effective Date: 06/20/01  
-----

SECTION III - HAZARDS IDENTIFICATION  
-----

Permissible Exposure Limits for Product:  
Not established for product. See Section II.

ROUTE OF ENTRY AND EFFECTS OF OVEREXPOSURE

ROUTE OF ENTRY:

Inhalation and dermal.

INHALATION:

Vapor or fume will irritate the nose and throat.

EYE CONTACT:

Vapor or fume can irritate the eyes.

SKIN CONTACT:

Substance can cause moderate irritation.

INGESTION:

Ingestion can cause irritation of gastro-intestinal tract.

DELAYED EFFECTS:

Repeated overexposure may cause headaches, dizziness, drowsiness, unconsciousness and central nervous system effects.

Contains an ingredient listed as known or suspected carcinogen?

NTP: No

OSHA: No

IARC: No  
-----

SECTION IV - FIRST AID MEASURES  
-----

INHALATION:

If inhaled, remove from area to fresh air. If not breathing, give artificial respiration. Get immediate medical attention. If breathing is difficult, transport to medical facility and, if available, give supplemental oxygen.

EYE CONTACT:

For eye contact, immediately flush eyes for at least 15 minutes with running water. Hold eyelids apart to ensure rinsing of the entire eye surface and lids with water. Get immediate medical attention.

SKIN CONTACT:

For skin contact, wipe excess material with dry towel. Then wash exposed areas with plenty of water, and soap if available, for several minutes. Get medical attention if irritation occurs.

INGESTION:

If swallowed dilute by giving two(2) glasses of water to drink. Get immediate medical attention. Never give anything by mouth to an  
-----

-----  
MATERIAL SAFETY DATA SHEET

PR-2050 B-1/2, Part B  
FM5456

Effective Date: 06/20/01  
-----

unconscious person.

GENERAL:

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.  
-----

SECTION V - FIRE AND EXPLOSION HAZARD IDENTIFICATION  
-----

FLASHPOINT: 150 F 65.55 C Method: Setaflash  
LEL (%): N/Av UEL (%): N/Av

FLAMMABILITY CLASSIFICATION:

Combustible

FIRE AND EXPLOSION HAZARDS:

Decomposition and combustion products may be hazardous. High temperatures may cause pressure build-up in closed containers. Vapors may accumulate in inadequately ventilated or confined areas. Vapors may form explosive mixture with air. Vapors are heavier than air and may travel long distances. Flashback or flame to the handling site may occur. Closed containers may explode when exposed to extreme heat.

EXTINGUISHING MEDIA:

Carbon dioxide, dry chemical, foam.

FIRE FIGHTING PROCEDURES:

Water spray may be ineffective. Cool fire exposed containers with water. Fog nozzles are preferable. Wear NIOSH/MSHA approved self-contained breathing apparatus and complete protective clothing to prevent contact with skin and eyes.  
-----

SECTION VI - ACCIDENTAL RELEASE MEASURES  
-----

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Remove all ignition sources. Wear an air-supplied respirator for an unventilated spill. Cover with absorbent. Scoop into containers using non-sparking tools. Clean up residue with a suitable cleaning solvent. Wear appropriate personal protective equipment (See Section VIII).  
-----

-----  
MATERIAL SAFETY DATA SHEET

PR-2050 B-1/2, Part B  
FM5456

Effective Date: 06/20/01  
-----

SECTION VII - HANDLING AND STORAGE  
-----

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Keep container tightly closed. Store in a dry location. Wear proper personal protective equipment (See Section VIII). Wash thoroughly after handling and before smoking or eating.  
-----

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION  
-----

ENGINEERING CONTROLS:

Good general mechanical ventilation.

RESPIRATORY PROTECTION:

When spraying or applying in any circumstances likely to produce airborne levels of solvent vapors in excess of the TLV, use an organic vapor cartridge or air-supplied respirator.

EYE PROTECTION:

Chemical goggles or full-face shield.

SKIN PROTECTION:

Solvent resistant gloves.

GENERAL:

Safety shower, eye wash station and washing facilities should be available. When using in circumstances where skin contact is likely, use complete protective garments.  
-----

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES  
-----

Appearance:	Cream
Physical State:	Paste
Low Boiling Point:	N/Av
High Boiling Point:	N/Av
Evaporation Rate:	Slower than n-butyl acetate
Vapor Density:	Heavier than air
% Volatiles by Volume:	2.76
Specific Gravity:	1.47
Liquid Density:	Heavier than water
Weight Per Gallon:	12.25
VOC (GR/L):	24
VOC (GR/L, Combined):	36

-----

-----  
MATERIAL SAFETY DATA SHEET

PR-2050 B-1/2, Part B  
FM5456

Effective Date: 06/20/01  
-----

SECTION X - STABILITY AND REACTIVITY  
-----

STABILITY:

Stable.

HAZARDOUS POLYMERIZATION:

Will not occur.

INCOMPATIBILITY:

Strong oxidizing agents.

CONDITIONS TO AVOID:

See incompatibilities above.

HAZARDOUS DECOMPOSITION PRODUCTS:

Oxides of carbon and nitrogen, sulfur dioxide, traces of hydrogen sulfide.  
-----

SECTION XI - TOXICOLOGICAL INFORMATION  
-----

ACUTE ORAL, DERMAL AND INHALATION EFFECTS (LD50 AND LC50):

CAS NUMBER	LD50	LC50
REF00000005	N/Av	N/Av
001330-20-7	5400 mg/kg, oral, rat	6350 ppm, rat, 4hr.
061788-32-7	10000 mg/kg, oral, rat	4.7 mg/L, rat, 4hr.

-----

NOTICE:

There are no data available on the product itself.  
-----

SECTION XII - ECOLOGICAL INFORMATION  
-----

NOTICE:

There are no data available on the product itself.  
-----

-----  
MATERIAL SAFETY DATA SHEET

PR-2050 B-1/2, Part B  
FM5456

Effective Date: 06/20/01  
-----

SECTION XIII - DISPOSAL CONSIDERATIONS  
-----

WASTE DISPOSAL METHOD:

When disposing of this material, ensure that it is packaged, stored, transported, and otherwise handled in accordance with local, state, and federal regulations.  
-----

SECTION XIV - TRANSPORT INFORMATION  
-----

DOT (Non-Bulk):

PROPER SHIPPING NAME: Not regulated  
HAZARD CLASS: Not Applicable  
UN NUMBER: Not Available

SPECIAL NOTES:

None  
-----

SECTION XV - REGULATORY INFORMATION  
-----

TSCA Section 8(b) - Inventory Status:

All ingredients in this product are listed in the TSCA Inventory or are exempt from listing.

CANADIAN EPA - DSL Inventory Status:

The DSL status of this product is unknown at this time.

SARA Title III Section 313 - Toxic Chemical List (TCL):

This product contains a toxic chemical for routine annual "Toxic Chemical Release Reporting" under Section 313 (40 CFR 372). This information must be included in all MSDS's copied or distributed for this product.

001330-20-7 Xylene

SARA Title III Section 302 - CERCLA:

This product contains the following chemicals regulated under Section 302 as extremely hazardous substance(s) for emergency release notification (CERCLA List).

-----  
MATERIAL SAFETY DATA SHEET

PR-2050 B-1/2, Part B  
FM5456

Effective Date: 06/20/01  
-----

001330-20-7 Xylene

1000

CALIFORNIA PROPOSITION 65 - Reportable ingredients:

Chemicals known by the state of CA to cause cancer:

This product contains the following chemical which is known to the state of California to cause cancer.

000050-00-0 Formaldehyde

Chemicals known by the state of CA to cause reproductive toxicity:

This product does not contain any chemicals currently on the California list of known Reproductive Toxins.

TSCA Section 12(b) - Export Notification:

This product contains following chemical that required annual or one time export notification per chemical and per country.

000108-95-2 Phenol

CLEAN AIR ACT - Hazardous Air Pollutants (CAA Section 112):

This product contains the following chemicals regulated under Section 112 for National Emission Standards of Hazardous Air Pollutants notification.

000050-00-0 Formaldehyde

000108-95-2 Phenol

001330-20-7 Xylene

Pennsylvania Right to Know - Reportable Ingredients:

The following is required composition information. Also, review Section II for additional information for other chemicals.

001317-65-3 Limestone

001330-20-7 Xylene

061788-32-7 Hydrogenated Terphenyl

New Jersey Right to Know - Reportable Ingredients:

The following is required composition information. Also, review Section II for additional information for other chemicals.

001330-20-7 Xylene



-----  
MATERIAL SAFETY DATA SHEET

PR-2050 B-1/2, Part B  
FM5456

Effective Date: 06/20/01  
-----

SECTION XVI - OTHER INFORMATION  
-----

Effective Date: 06/20/01      Supersedes Date: 06/20/2001  
Revision Number: 00  
Revision Reason: New Product

The information in this MSDS was obtained from sources which we believe to be reliable. However, since much of the information has been received from sources outside the company, it is provided without any warranty, expressed or implied, regarding its correctness, or suitability for specific situations. The conditions of handling, storage, use, and disposal of this product are beyond our control and may be beyond our knowledge. The user has the sole responsibility to determine the suitability of the material for any use, and the manner and conditions of use. Therefore, we cannot assume responsibility and expressly disclaim liability for loss, damage, injury, or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. Effects can be aggravated by other materials and/or this material may aggravate or add to the effects of other materials.

-----

End of Document