

-----  
MATERIAL SAFETY DATA SHEET

Pro-Seal 870 B-1/2, Part A  
FM4636B

Effective Date: 01/10/01  
-----

SECTION I - MANUFACTURER AND PRODUCT INFORMATION  
-----

PRC-DeSoto International, Inc.  
A PPG Industries Company  
5430 San Fernando Road  
P.O. Box 1800  
Glendale, CA 91209

Information Phone: (818) 240-2060  
Emergency Phone: (800) 228-5635  
CHEMTREC: (800) 424-9300

Trade Name: Pro-Seal 870 B-1/2, Part A  
Accelerator component  
Product Code: FM4636B  
Form ID No: A05  
Product Class: Manganese dioxide dispersion  
Synonyms: S-4636

HMIS HAZARD RATING  
HEALTH - 3  
FLAMMABILITY - 1  
REACTIVITY - 0  
PPE - G  
None(0)--->Extreme(4)  
-----

SECTION II - COMPOSITION  
-----

INGREDIENTS INFORMATION

CAS NUMBER	Wt %	CHEMICAL IDENTITY
001313-13-9	30 - 60	Manganese Dioxide
061788-32-7	30 - 60	Hydrogenated Terphenyl
013423-61-5	10 - 30	Magnesium Chromate, X-Hydrate
026140-60-3	< 5	Terphenyls
000102-06-7	< 5	1,3-Diphenyl Guanidine
014807-96-6	< 5	Talc

EXPOSURE LIMITS

CAS NUMBER	EXPOSURE LIMITS (ppm)				
	ACGIH TLVs		OSHA PELs		
	TWA	STEL	TWA	STEL	
001313-13-9	0.2 mg/m3	N/E	5	N/E	S
061788-32-7	0.5	N/E	0.5	N/E	S
013423-61-5	0.05 mg/m3	N/E	0.05 mg/m3	N/E	S
026140-60-3	0.5	N/E	0.5	N/E	S
000102-06-7	10 mg/m3	N/E	15 mg/m3	N/E	S
014807-96-6	2 mg/m3	N/E	2 mg/m3	N/E	S

Footnotes

(S) Occupational Exposure Standard  
(R) Supplier's Recommended Limit  
-----

-----  
MATERIAL SAFETY DATA SHEET

Pro-Seal 870 B-1/2, Part A  
FM4636B

Effective Date: 01/10/01  
-----

N/Av = Not Available

N/Ap = Not Applicable

N.E. = Not Established

NotknownXXX = CAS Number is not known.  
-----

SECTION III - HAZARDS IDENTIFICATION  
-----

Permissible Exposure Limits for Product:

Not established for product. See Section II.

ROUTE OF ENTRY AND EFFECTS OF OVEREXPOSURE

ROUTE OF ENTRY:

Inhalation and dermal.

INHALATION:

Vapor will irritate nose, throat and respiratory tract. High vapor concentration may cause dizziness, drowsiness and fatigue.

EYE CONTACT:

Vapor or substance is severely irritating to eyes and cause redness and tearing.

SKIN CONTACT:

Substance can cause severe skin irritation with drying, defatting, splitting and cracking on repeated contact.

INGESTION:

Substance can cause irritation of gastro-intestinal tract followed by nausea, vomiting and abdominal discomfort.

DELAYED EFFECTS:

Repeated overexposure may cause headaches, dizziness, drowsiness, unconsciousness and central nervous system effects.

Contains an ingredient listed as known or suspected carcinogen?

NTP: Yes

OSHA: No

IARC: Yes  
-----

SECTION IV - FIRST AID MEASURES  
-----

INHALATION:

If inhaled, remove from area to fresh air. If not breathing, give artificial respiration. Get immediate medical attention. If breathing is difficult, transport to medical facility and, if available, give supplemental oxygen.

EYE CONTACT:

For eye contact, immediately flush eyes for at least 15 minutes with running water. Hold eyelids apart to ensure rinsing of the entire eye surface and lids with water. Get immediate medical  
-----

-----  
MATERIAL SAFETY DATA SHEET

Pro-Seal 870 B-1/2, Part A  
FM4636B

Effective Date: 01/10/01  
-----

attention.

SKIN CONTACT:

For skin contact, wipe excess material with dry towel. Then wash exposed areas with plenty of water, and soap if available, for several minutes. Get medical attention if irritation occurs.

INGESTION:

If swallowed dilute by giving two(2) glasses of water to drink. Get immediate medical attention. Never give anything by mouth to an unconscious person.

GENERAL:

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.  
-----

SECTION V - FIRE AND EXPLOSION HAZARD IDENTIFICATION  
-----

FLASHPOINT: N/App

Method: Not Applicable

LEL (%): N/Av

UEL (%): N/Av

FLAMMABILITY CLASSIFICATION:

Not flammable.

FIRE AND EXPLOSION HAZARDS:

Decomposition and combustion products may be hazardous. No unusual hazards known.

EXTINGUISHING MEDIA:

Carbon dioxide, dry chemical, foam, water fog.

FIRE FIGHTING PROCEDURES:

Use complete personal protection. Use water to cool heat exposed containers.  
-----

SECTION VI - ACCIDENTAL RELEASE MEASURES  
-----

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Dike and cover spill with non-oxidizable absorbent. Scoop into containers. Sprinkle sodium thiosulfate on the residue and work in. Scoop into disposal container. Clean up with water. Wear appropriate personal protective equipment (See Section VIII).  
-----

-----  
MATERIAL SAFETY DATA SHEET

Pro-Seal 870 B-1/2, Part A  
FM4636B

Effective Date: 01/10/01  
-----

SECTION VII - HANDLING AND STORAGE  
-----

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Keep container tightly closed. Store in a dry location. Wear proper personal protective equipment (See Section VIII). Wash thoroughly after handling and before smoking or eating.  
-----

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION  
-----

ENGINEERING CONTROLS:

Good general mechanical ventilation.

RESPIRATORY PROTECTION:

Not normally required.

EYE PROTECTION:

Safety glasses.

SKIN PROTECTION:

Chemically resistant gloves.

GENERAL:

Safety shower, eye wash station and washing facilities should be available. When using in circumstances where skin contact is likely, use complete protective garments.  
-----

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES  
-----

Appearance:	Black
Physical State:	Paste
Low Boiling Point:	N/Av
High Boiling Point:	N/Av
Evaporation Rate:	Non-volatile
Vapor Density:	Non-volatile
% Volatiles by Volume:	0
Specific Gravity:	1.89
Liquid Density:	Heavier than water
Weight Per Gallon:	15.74
VOC (GR/L):	N/Av
VOC (GR/L, Combined):	N/Av

-----

-----  
MATERIAL SAFETY DATA SHEET

Pro-Seal 870 B-1/2, Part A  
FM4636B

Effective Date: 01/10/01  
-----

SECTION X - STABILITY AND REACTIVITY  
-----

STABILITY:

Stable.

HAZARDOUS POLYMERIZATION:

Will not occur.

INCOMPATIBILITY:

Easily oxidizable materials.

CONDITIONS TO AVOID:

See incompatibilities above.

HAZARDOUS DECOMPOSITION PRODUCTS:

Oxides of carbon and nitrogen, manganese compounds and chromium compounds.  
-----

SECTION XI - TOXICOLOGICAL INFORMATION  
-----

ACUTE ORAL, DERMAL AND INHALATION EFFECTS (LD50 AND LC50):

CAS NUMBER	LD50	LC50
001313-13-9	14900 mg/kg, oral, rat	N/AV.
061788-32-7	10000 mg/kg, oral, rat	4.7 mg/L, rat, 4hr.
013423-61-5	5000 mg/kg, oral, rat	N/AV.
026140-60-3	10000 mg/kg, oral, rat	4.7 mg/L, rat, 4hr.
000102-06-7	350 mg/kg, oral, rat	N/AV.
014807-96-6	5000 mg/kg, oral, rat	N/AV.

  
-----

Carcinogenicity:

Chromium Compounds (Magnesium chromate):

NTP and IARC have determined that there is sufficient evidence for the carcinogenicity of hexavalent chromium compounds both in humans and experimental animals. Prolonged or repeated eye contact may cause conjunctivitis. Prolonged or repeated skin contact, especially with broken skin, may cause "chrome sores". Prolonged or repeated inhalation of mist or fume may cause ulceration and perforation of nasal septum. Prolonged inhalation may cause liver damage.

NOTICE:

There are no data available on the product itself.  
-----

-----  
MATERIAL SAFETY DATA SHEET

Pro-Seal 870 B-1/2, Part A  
FM4636B

Effective Date: 01/10/01  
-----

SECTION XII - ECOLOGICAL INFORMATION  
-----

NOTICE:

There are no data available on the product itself.  
-----

SECTION XIII - DISPOSAL CONSIDERATIONS  
-----

WASTE DISPOSAL METHOD:

When disposing of this material, ensure that it is packaged, stored, transported, and otherwise handled in accordance with local, state, and federal regulations.

EPA WASTE NUMBERS:

D-007 (Chromium)  
-----

SECTION XIV - TRANSPORT INFORMATION  
-----

DOT (Non-Bulk):

PROPER SHIPPING NAME: Not regulated  
HAZARD CLASS: Not Applicable  
UN NUMBER: Not Available

SPECIAL NOTES:

None  
-----

SECTION XV - REGULATORY INFORMATION  
-----

TSCA Section 8(b) - Inventory Status:

All ingredients in this product are listed in the TSCA Inventory or are exempt from listing.

CANADIAN EPA - DSL Inventory Status:

The DSL status of this product is unknown at this time.

SARA Title III Section 313 - Toxic Chemical List (TCL):

This product contains a toxic chemical for routine annual "Toxic Chemical Release Reporting" under Section 313 (40 CFR 372). This information must be included in all MSDS's copied or distributed for this product.  
-----

-----  
MATERIAL SAFETY DATA SHEET

Pro-Seal 870 B-1/2, Part A  
FM4636B

Effective Date: 01/10/01  
-----

001313-13-9 Manganese Dioxide

SARA Title III Section 302 - CERCLA:

This product contains no chemical regulated under Section 302 as extremely hazardous chemicals for emergency release notification (CERCLA List).

CALIFORNIA PROPOSITION 65 - Reportable ingredients:

Chemicals known by the state of CA to cause cancer:

This product contains the following chemical which is known to the state of California to cause cancer.

013423-61-5 Magnesium Chromate, X-Hydrate

Chemicals known by the state of CA to cause reproductive toxicity:

This product does not contain any chemicals currently on the California list of known Reproductive Toxins.

TSCA Section 12(b) - Export Notification:

This product does not contain any chemicals subject to Section 12(b) export notification.

CLEAN AIR ACT - Hazardous Air Pollutants (CAA Section 112):

This product contains the following chemicals regulated under Section 112 for National Emission Standards of Hazardous Air Pollutants notification.

001313-13-9 Manganese Dioxide

013423-61-5 Magnesium Chromate, X-Hydrate

Pennsylvania Right to Know - Reportable Ingredients:

The following is required composition information. Also, review Section II for additional information for other chemicals.

001310-73-2 Sodium Hydroxide

013423-61-5 Magnesium Chromate, X-Hydrate

014807-96-6 Talc

026140-60-3 Terphenyls

061788-32-7 Hydrogenated Terphenyl

-----  
MATERIAL SAFETY DATA SHEET

Pro-Seal 870 B-1/2, Part A  
FM4636B

Effective Date: 01/10/01  
-----

New Jersey Right to Know - Reportable Ingredients:

The following is required composition information. Also, review Section II for additional information for other chemicals.

001313-13-9	Manganese Dioxide
014807-96-6	Talc

-----

SECTION XVI - OTHER INFORMATION  
-----

Effective Date: 01/10/01      Supersedes Date: 02/04/1999  
Revision Number: 01

The information in this MSDS was obtained from sources which we believe to be reliable. However, since much of the information has been received from sources outside the company, it is provided without any warranty, expressed or implied, regarding its correctness, or suitability for specific situations. The conditions of handling, storage, use, and disposal of this product are beyond our control and may be beyond our knowledge. The user has the sole responsibility to determine the suitability of the material for any use, and the manner and conditions of use. Therefore, we cannot assume responsibility and expressly disclaim liability for loss, damage, injury, or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. Effects can be aggravated by other materials and/or this material may aggravate or add to the effects of other materials.

-----

End of Document

-----  
MATERIAL SAFETY DATA SHEET

Pro-Seal 870 B-1/2, Part B  
FM4933

Effective Date: 09/10/02

-----  
SECTION I - MANUFACTURER AND PRODUCT INFORMATION  
-----

PRC-DeSoto International, Inc.  
A PPG Industries Company  
5430 San Fernando Road  
P.O. Box 1800  
Glendale, CA 91209

Information Phone: (818) 240-2060  
Emergency Phone: (800) 228-5635  
Outside of USA: +(651) 632-9265  
CHEMTREC: (800) 424-9300

Trade Name: Pro-Seal 870 B-1/2, Part B  
Base component

Product Code: FM4933  
Form ID No: B04  
Product Class: Filled Modified polysulfide resin  
Synonyms: P-4933

HMIS HAZARD RATING  
HEALTH - 2  
FLAMMABILITY - 3  
REACTIVITY - 0  
PPE - H  
None(0)--->Extreme(4)

-----  
SECTION II - COMPOSITION  
-----

INGREDIENTS INFORMATION

CAS NUMBER	Wt %	CHEMICAL IDENTITY
068611-50-7	30 - 60	Liquid Polysulphide Polymer with Thiol End Groups
000471-34-1	10 - 30	Calcium Carbonate
REF00000006	1 - 10	Modified polysulfide polymer
067762-90-7	1 - 10	Amorphous Fumed Silica
013463-67-7	1 - 10	Titanium Dioxide @
000108-88-3	< 5	Toluene
020941-65-5	< 2	Tellurium Diethyldithiocarbamate

EXPOSURE LIMITS

CAS NUMBER	EXPOSURE LIMITS (ppm)				S
	ACGIH TLVs		OSHA PELs		
	TWA	STEL	TWA	STEL	
068611-50-7	N/E	N/E	N/E	N/E	
000471-34-1	10	N/E	15	N/E	S
REF00000006	N/E	N/E	N/E	N/E	
067762-90-7	10 mg/m3	N/E	N/E	N/E	S
013463-67-7	10 mg/m3	N/E	10 mg/m3	N/E	S
000108-88-3	50	N/E	100	N/E	S
020941-65-5	10 mg/m3	N/E	10 mg/m3	N/E	S

-----  
MATERIAL SAFETY DATA SHEET

Pro-Seal 870 B-1/2, Part B  
FM4933

Effective Date: 09/10/02  
-----

Footnotes

- (S) Occupational Exposure Standard
- (R) Supplier's Recommended Limit

N/Av = Not Available

N/Ap = Not Applicable

N.E. = Not Established

NotknownXXX = CAS Number is not known.  
-----

SECTION III - HAZARDS IDENTIFICATION  
-----

Permissible Exposure Limits for Product:

Not established for product. See Section II.

ROUTE OF ENTRY AND EFFECTS OF OVEREXPOSURE

ROUTE OF ENTRY:

Inhalation and dermal.

INHALATION:

Vapor or fume will irritate the nose and throat.

EYE CONTACT:

Vapor or fume can irritate the eyes.

SKIN CONTACT:

Substance can cause moderate irritation.

INGESTION:

Ingestion can cause irritation of gastro-intestinal tract.

DELAYED EFFECTS:

Repeated overexposure may cause headaches, dizziness, drowsiness, unconsciousness and central nervous system effects.

Contains an ingredient listed as known or suspected carcinogen?

NTP: No

OSHA: No

IARC: No  
-----

SECTION IV - FIRST AID MEASURES  
-----

INHALATION:

If inhaled, remove from area to fresh air. If not breathing, give artificial respiration. Get immediate medical attention. If breathing is difficult, transport to medical facility and, if available, give supplemental oxygen.

EYE CONTACT:

For eye contact, immediately flush eyes for at least 15 minutes with running water. Hold eyelids apart to ensure rinsing of the entire eye surface and lids with water. Get immediate medical  
-----

-----  
MATERIAL SAFETY DATA SHEET

Pro-Seal 870 B-1/2, Part B  
FM4933

Effective Date: 09/10/02  
-----

attention.

SKIN CONTACT:

For skin contact, wipe excess material with dry towel. Then wash exposed areas with plenty of water, and soap if available, for several minutes. Get medical attention if irritation occurs.

INGESTION:

If swallowed dilute by giving two(2) glasses of water to drink. Get immediate medical attention. Never give anything by mouth to an unconscious person.

GENERAL:

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.  
-----

SECTION V - FIRE AND EXPLOSION HAZARD IDENTIFICATION  
-----

FLASHPOINT: 95 F 35 C

Method: Setaflash

LEL (%): N/Av

UEL (%): N/Av

FLAMMABILITY CLASSIFICATION:

Flammable

FIRE AND EXPLOSION HAZARDS:

Decomposition and combustion products may be hazardous. High temperatures may cause pressure build-up in closed containers. Vapors may accumulate in inadequately ventilated or confined areas. Vapors may form explosive mixture with air. Vapors are heavier than air and may travel long distances. Flashback or flame to the handling site may occur. Closed containers may explode when exposed to extreme heat.

EXTINGUISHING MEDIA:

Carbon dioxide, dry chemical, foam.

FIRE FIGHTING PROCEDURES:

Water spray may be ineffective. Cool fire exposed containers with water. Fog nozzles are preferable. Wear NIOSH/MSHA approved self-contained breathing apparatus and complete protective clothing to prevent contact with skin and eyes.  
-----

-----  
MATERIAL SAFETY DATA SHEET

Pro-Seal 870 B-1/2, Part B  
FM4933

Effective Date: 09/10/02  
-----

SECTION VI - ACCIDENTAL RELEASE MEASURES  
-----

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Remove all ignition sources. Wear an air-supplied respirator for an unventilated spill. Cover with absorbent. Scoop into containers using non-sparking tools. Clean up residue with a suitable cleaning solvent. Wear appropriate personal protective equipment (See Section VIII).

-----

SECTION VII - HANDLING AND STORAGE  
-----

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Keep container tightly closed. Isolate from heat, electrical equipment, sparks and flame. Use grounding and bonding procedures during transfer. Do not store above 120 degrees F. Vapors of this product are heavier than air and may collect in low or confined areas. Empty drums may contain explosive vapors. Do not cut, puncture, or weld on or near drum. Wear proper personal protective equipment (See Section VIII). Wash thoroughly after handling and before smoking or eating.

-----

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION  
-----

ENGINEERING CONTROLS:

Local and/or general ventilation as required to maintain hazardous ingredients below recommended (ACGIH-TLV) or regulated (OSHA-PEL) limits.

RESPIRATORY PROTECTION:

When spraying or applying in any circumstances likely to produce airborne levels of solvent vapors in excess of the TLV, use an organic vapor cartridge or air-supplied respirator.

EYE PROTECTION:

Chemical goggles or full-face shield.

SKIN PROTECTION:

Solvent resistant gloves.

GENERAL:

Safety shower, eye wash station and washing facilities should be available. When using in circumstances where skin contact is likely, use complete protective garments.

-----

-----  
MATERIAL SAFETY DATA SHEET

Pro-Seal 870 B-1/2, Part B  
FM4933

Effective Date: 09/10/02  
-----

-----  
SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES  
-----

Appearance: Beige  
Physical State: Thixotropic paste  
Low Boiling Point: N/Av  
High Boiling Point: N/Av  
Evaporation Rate: Slower than n-butyl acetate  
Vapor Density: Heavier than air  
% Volatiles by Volume: 5.7  
Specific Gravity: 1.48  
Liquid Density: Heavier than water  
Weight Per Gallon: 12.33  
VOC (GR/L): 132  
VOC (GR/L, Combined): 116  
-----

-----  
SECTION X - STABILITY AND REACTIVITY  
-----

STABILITY:

Stable.

HAZARDOUS POLYMERIZATION:

Will not occur.

INCOMPATIBILITY:

Strong oxidizing agents.

CONDITIONS TO AVOID:

See incompatibilities above.

HAZARDOUS DECOMPOSITION PRODUCTS:

Oxides of carbon and nitrogen, sulfur dioxide, traces of hydrogen sulfide.  
-----

-----  
MATERIAL SAFETY DATA SHEET

Pro-Seal 870 B-1/2, Part B  
FM4933

Effective Date: 09/10/02  
-----

SECTION XI - TOXICOLOGICAL INFORMATION  
-----

ACUTE ORAL, DERMAL AND INHALATION EFFECTS (LD50 AND LC50):

CAS NUMBER	LD50	LC50
068611-50-7	5000 mg/kg, oral, rat	N/AV.
000471-34-1	2000 mg/kg, oral, rat	N/AV.
REF00000006	N/Av	N/Av
067762-90-7	5000 mg/kg, oral, rat	4.9 mg/L, rat, 4hr.
013463-67-7	7500 mg/kg, oral, rat	N/AV.
000108-88-3	2600 mg/kg, oral, rat	8800 ppm, rat, 4hr.
020941-65-5	5000 mg/kg, oral, rat	0.51 mg/L, rat, 4hr.

-----

NOTICE:

There are no data available on the product itself.  
-----

SECTION XII - ECOLOGICAL INFORMATION  
-----

NOTICE:

There are no data available on the product itself.  
-----

SECTION XIII - DISPOSAL CONSIDERATIONS  
-----

WASTE DISPOSAL METHOD:

When disposing of this material, ensure that it is packaged, stored, transported, and otherwise handled in accordance with local, state, and federal regulations.

EPA WASTE NUMBERS:

D-001 (Ignitable)  
-----

-----  
MATERIAL SAFETY DATA SHEET

Pro-Seal 870 B-1/2, Part B  
FM4933

Effective Date: 09/10/02  
-----

SECTION XIV - TRANSPORT INFORMATION  
-----

DOT (Non-Bulk):

PROPER SHIPPING NAME: Not regulated  
HAZARD CLASS: Not Applicable  
UN NUMBER: Not Available

SPECIAL NOTES:

Testing conducted according to the U.S. DOT and IATA regulations, demonstrated that this material is not classified as a flammable liquid and is not sufficiently ignitable to be classified as a flammable solid. Therefore, it is not regulated as a flammable material for transportation.  
-----

SECTION XV - REGULATORY INFORMATION  
-----

TSCA Section 8(b) - Inventory Status:

All ingredients in this product are listed in the TSCA Inventory or are exempt from listing.

CANADIAN EPA - DSL Inventory Status:

The DSL status of this product is unknown at this time.

SARA Title III Section 313 - Toxic Chemical List (TCL):

This product contains a toxic chemical for routine annual "Toxic Chemical Release Reporting" under Section 313 (40 CFR 372). This information must be included in all MSDS's copied or distributed for this product.

000108-88-3 Toluene

SARA Title III Section 302 - CERCLA:

This product contains the following chemicals regulated under Section 302 as extremely hazardous substance(s) for emergency release notification (CERCLA List).

000108-88-3 Toluene

1000

-----  
MATERIAL SAFETY DATA SHEET

Pro-Seal 870 B-1/2, Part B  
FM4933

Effective Date: 09/10/02  
-----

CALIFORNIA PROPOSITION 65 - Reportable ingredients:

Chemicals known by the state of CA to cause cancer:

This product contains the following chemical which is known to the state of California to cause cancer.

000050-00-0      Formaldehyde

Chemicals known by the state of CA to cause reproductive toxicity:

This product contains the following chemical which is known to the state of California to cause reproductive toxicity.

000108-88-3      Toluene

TSCA Section 12(b) - Export Notification:

This product contains following chemical that required annual or one time export notification per chemical and per country.

000108-95-2      Phenol

CLEAN AIR ACT - Hazardous Air Pollutants (CAA Section 112):

This product contains the following chemicals regulated under Section 112 for National Emission Standards of Hazardous Air Pollutants notification.

000050-00-0      Formaldehyde

000108-88-3      Toluene

000108-95-2      Phenol

Pennsylvania Right to Know - Reportable Ingredients:

The following is required composition information. Also, review Section II for additional information for other chemicals.

000108-88-3      Toluene

000137-26-8      Tetramethylthiuram Disulfide

007757-82-6      Sodium Sulfate

013463-67-7      Titanium Dioxide @

New Jersey Right to Know - Reportable Ingredients:

The following is required composition information. Also, review Section II for additional information for other chemicals.

000108-88-3      Toluene

013463-67-7      Titanium Dioxide @

-----  
MATERIAL SAFETY DATA SHEET

Pro-Seal 870 B-1/2, Part B  
FM4933

Effective Date: 09/10/02  
-----  
-----

SECTION XVI - OTHER INFORMATION  
-----

Effective Date: 09/10/02      Supersedes Date: 01/10/2001  
Revision Number: 02  
Revision Reason: Formula & Section 5 Update

The information in this MSDS was obtained from sources which we believe to be reliable. However, since much of the information has been received from sources outside the company, it is provided without any warranty, expressed or implied, regarding its correctness, or suitability for specific situations. The conditions of handling, storage, use, and disposal of this product are beyond our control and may be beyond our knowledge. The user has the sole responsibility to determine the suitability of the material for any use, and the manner and conditions of use. Therefore, we cannot assume responsibility and expressly disclaim liability for loss, damage, injury, or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. Effects can be aggravated by other materials and/or this material may aggravate or add to the effects of other materials.

-----

End of Document