Solutia Inc.

Material Safety Data Sheet

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:

SKYDROL® LD4 Fire resistant hydraulic fluid

Reference Number:

00000000183

Date: 11/10/2005

Company Information:

United States:

Solutia Inc. 575 Maryville Center Drive, P.O. Box 66760 St. Louis, MO 63166-6760 Emergency telephone: Chemtrec: 1-800-424-9300 Non-Emergency telephone: 1-314-674-6661

Mexico:

Solutia MEXICO, S. DE R.L. DE C.V. Paseo de la Reforma No. 2654 Piso 3-A Col. Lomas Altas C.P. 11950 Mexico D.F. Emergency telephone: SETIQ: (in Mexico) 01-800-002-1400 Non-Emergency telephone: (in Mexico) 01-55-5259-6800

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Form:	oily, liquid
Colour:	clear to purple
Odour:	odourless

WARNING STATEMENTS

WARNING! Causes eye irritation Causes skin irritation Causes respiratory tract irritation Contains material which may cause urinary bladder damage based on animal data Limited evidence of a carcinogenic effect.

POTENTIAL HEALTH EFFECTS

Likely routes of exposure: eye and skin contact

Canada:

Solutia Canada Inc. 6800 St. Patrick Street LaSalle, PQ H8N 2H3 Emergency telephone: CANUTEC: 1-613-996-66666 Non-Emergency telephone: 1-314-674-6661

<u>Brazil</u>:

Solutia Brazil Ltd. Avenue Carlos Marcondes, 1200 CEP: 12241-420-São José dos Campos/SP-Brazil Emergency telephone: 55 12 3932 7100 (PABX) Non-Emergency telephone: 55 11 3365 1800 (PABX) Product name: SKYDROL® LD4 Fire resistant hydraulic fluid Solutia Inc. Material Safety Data Sheet Reference Number: 00000000183

	inhalation
Eye contact:	Highly irritating to eyes.
Skin contact:	Highly irritating to skin. No more than slightly toxic if absorbed. Repeated contact may cause a drying, solvent like action on the skin.
Inhalation:	Severely irritating if inhaled. No more than slightly toxic if inhaled. Significant adverse health effects are not expected to develop under normal conditions of exposure.
Ingestion:	No more than slightly toxic if swallowed. Significant adverse health effects are not expected to develop if only small amounts (less than a mouthful) are swallowed.
Signs and symptoms of overexposure:	coughing sneezing headache nausea/vomiting
Target organs/systems:	Contains material which may cause urinary bladder damage based on animal data

Refer to Section 11 for toxicological information.

3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Components</u>	CAS No.	<u>Average</u> concentration	Concentration range	<u>Units</u>
tributyl phosphate	126-73-8	58.2	<u> </u>	%
dibutyl phenyl phosphate	2528-36-1		20.0 - 30.0	%
butyl diphenyl phosphate	2752-95-6		5.0 - 10.0	%
2-ethylhexyl 7-oxabicyclo[4.1.0] heptane-	62256-00-2		<=10.0	%
3-carboxylate				
2,6-di-tert-butyl-p-cresol	128-37-0		1.0 - 5.0	%

4. FIRST AID MEASURES

If in eyes:	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove any contact lenses. Get medical attention. Remove material from skin and clothing.
If on skin:	Immediately flush the area with plenty of water. Remove contaminated clothing. Wash skin gently with soap as soon as it is available. Get medical attention. Wash clothing before reuse.
If inhaled:	Remove patient to fresh air. If not breathing, give artificial respiration. If breathing is difficult give oxygen.

of

Remove material from eyes, skin and clothing.

If swallowed:	Immediate first aid is not likely to be required. A physician or Poison Control Center can be contacted for advice. Wash heavily contaminated clothing before reuse.
Notes to physicians:	After flushing eyes for at least 15 minutes, opthalmic preparations of sterile mineral or castor oil may be instilled one time in the exposed eye for relief of pain.

5. FIRE FIGHTING MEASURES

Fire point:	176 C	ASTM D-2155
Hazardous products of combu	stion:	None known;
Extinguishing media:		Water spray, foam, dry chemical, or carbon dioxide
Unusual fire and explosion ha	zards:	None known
Fire fighting equipment:		Firefighters, and others exposed, wear self-contained breathing apparatus. Equipment should be thoroughly decontaminated after use.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:	Use personal protection recommended in section 8.
Environmental precautions:	Keep out of drains and water courses.
Methods for cleaning up:	Contain large spills with dikes and transfer the material to appropriate containers for reclamation or disposal. Absorb remaining material or small spills with an inert material and then place in a chemical waste container. Flush spill area with water.

Refer to Section 13 for disposal information and Sections 14 and 15 for reportable quantity information.

7. HANDLING AND STORAGE

<u>Handling</u>

Avoid breathing vapour or mist. Avoid contact with eyes, skin and clothing. Use with adequate ventilation. Keep container closed. Wash thoroughly after handling.

Emptied containers retain vapour and product residue. Observe all recommended safety precautions until container is cleaned, reconditioned or destroyed. Do not reuse this container.

Storage General:

Stable under normal conditions of handling and storage.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Airborne exposure limits: (ml/m3 = ppm)

Product name: SKYDROL® LD4 Fire resistant hydraulic fluid Solutia Inc. Material Safety Data Sheet Reference Number: 00000000183

SKYDROL® LD4	No specific occupational exposure limit has been established.
tributyl phosphate	ACGIH TLV: 0.2 ml/m3 ; 2.2 mg/m3 ; ; 8-hr TWA OSHA PEL: 5 mg/m3 ; ; 8-hr TWA Mexican OEL: 0.2 ml/m3 ; 2.5 mg/m3 ; ; 8-hr TWA Mexican OEL: 0.4 ml/m3 ; 5 mg/m3 ; ; 15-min STEL
dibutyl phenyl phosphate	ACGIH TLV: 0.3 ml/m3 ; 3.5 mg/m3 ; skin * ; 8-hr TWA * skin absorption of this material may add to the overall exposure.
2,6-di-tert-butyl-p-cresol	ACGIH TLV: 2 mg/m3; ; 8-hr TWA OSHA PEL: 5 mg/m3; ; 8-hr TWA Mexican OEL: 10 mg/m3; ; 8-hr TWA Mexican OEL: 20 mg/m3; ; 15-min STEL
Eye protection:	Wear chemical goggles. Have eye flushing equipment available.
Hand protection:	Wear chemical resistant gloves. Consult the glove/clothing manufacturer to determine the appropriate type glove/clothing for a given application.
Body protection:	Wear suitable protective clothing. Wear full protective clothing if exposed to splashes. Consult the glove/clothing manufacturer to determine the appropriate type glove/clothing for a given application. Wash contaminated skin promptly. Launder contaminated clothing and clean protective equipment before reuse. Have safety shower available at locations where skin contact can occur. Wash thoroughly after handling.
Respiratory protection:	Avoid breathing vapour or mist. Use approved respiratory protection equipment (full facepiece recommended) when airborne exposure limits are exceeded. If used, full facepiece replaces the need for face shield and/or chemical goggles. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.
Ventilation:	Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. If practical, use local mechanical exhaust ventilation at sources of air contamination such as processing equipment.

Components referred to herein may be regulated by specific Canadian provincial legislation. Please refer to exposure limits legislated for the province in which the substance will be used.

9. PHYSICAL AND CHEMICAL PROPERTIES

Flash point:	160 C	Cleveland Open Cup
Autoignition temperature: Specific gravity:	398 C 1.004 - 1.014 @ 25 C	ASTM D-2155

Product name: SKYDROL® LD4 Fire resistant hydraulic fluid Solutia Inc. Material Safety Data Sheet Reference Number: 00000000183

Kinematic viscosity: 10.8 - 11.6 cSt @ 38 C

NOTE: These physical data are typical values based on material tested but may vary from sample to sample. Typical values should not be construed as a guaranteed analysis of any specific lot or as specifications for the product.

10. STABILITY AND REACTIVITY

Conditions to avoid:	Elevated temperatures
Materials to avoid:	Contact with strong oxidizing agents.
Hazardous reactions:	Hazardous polymerization does not occur.
Hazardous decomposition products:	phosphorus oxides (PxOy); carbon monoxide (CO); carbon dioxide

11. TOXICOLOGICAL INFORMATION

This product has been tested for toxicity. Results from Solutia sponsored studies or from the available public literature are described below.

Acute animal toxicity data

Oral:	LD50, rat, 2,100 mg/kg, Slightly toxic following oral administration.
Dermal:	LD50 , rabbit, $>$ 3,160 mg/kg , Practically nontoxic after skin application in animal studies.
Inhalation:	LC50, rat, > 5.8 mg/l, , No mortality or signs of toxicity at the highest level achievable.
Eye irritation:	rabbit, Slightly irritating to eyes (rabbit)., 24 h
Skin irritation:	rabbit, Moderately irritating to skin., 24 h
Skin sensitization:	Human experience, Predictive patch testing on human volunteers did not produce dermal sensitization.
Repeat dose toxicity:	rat, , inhalation, 28 days, , Repeated exposure produced eye irritation in animal models. Repeated exposure produced respiratory tract irritation in animal models. Produced effects on body weight, serum enzymes and/or organ weights in repeat dose studies.
Neurotoxicity:	chicken, gavage, acute, Brain cholinesterase inhibition.
Mutagenicity:	No genetic effects were observed in standard tests using bacterial and animal cells.

Components

Data from Solutia studies and/or the available scientific literature on the components of this material which have been identified as hazardous chemicals under the criteria of the OSHA Hazard Communication Standard (29 CFR 1910.1200) or the Canadian Hazardous Products Act are discussed below.

tributyl phosphate	Slightly toxic following oral administration. Practically nontoxic after skin application in animal studies. Slightly irritating to eyes (rabbit). Highly irritating to skin (rabbit). Produced no dermal sensitization (guinea pigs). Repeated oral administration produced multiple systemic effects. No delayed neurotoxicity was observed in animal models. This material produced tumours in laboratory animals at dose levels that exceed the maximum tolerated dose. The weight of the evidence indicates that this material is not mutagenic in in-vitro assays.
dibutyl phenyl phosphate	 Slightly toxic following oral administration. Practically nontoxic after skin application in animal studies. Practically non irritating to eyes (rabbit). Practically non irritating to skin (rabbit). Produced no dermal sensitization (guinea pigs). Repeated skin exposure produced irritation in animal studies. Produced effects on body weight, serum enzymes and/or organ weights in repeat dose studies. Repeated oral administration produced multiple organ effects. No delayed neurotoxicity was observed in animal models. No birth defects were noted in rats given the active ingredient orally during pregnancy. This material had no effect on reproduction or fertility. Produced developmental toxicity. The weight of the evidence indicates that this material is not mutagenic in in-vitro assays.
2,6-di-tert-butyl-p-cresol	Slightly irritating to skin, eyes and respiratory system in animal models. Produced effects on body weight, serum enzymes and/or organ weights in repeat dose studies. Both positive and negative responses observed in standard tests for genetic changes.
2-ethylhexyl 7- oxabicyclo[4.1.0] heptane-3-carboxylate	Slightly toxic following oral administration. Practically nontoxic after skin application in animal studies. Practically non irritating to eyes (rabbit). Slightly irritating to skin (rabbit). No mortality or signs of toxicity at the highest level tested. Produced dermal sensitization (guinea pigs). The weight of the evidence indicates that this material is not mutagenic in in-vitro assays. The weight of the evidence indicates that this material is mutagenic in in vivo assays.

12. ECOLOGICAL INFORMATION

Environmental Toxicity

Invertebrates	48 h, EC50	Water flea (Daphnia magna) 5.	5.8 mg/l
Fish:	,	Rainbow trout (Oncorhynchus m Fathead minnow (Pimephales pro	, 0

Algae:	96 h, EC50	Algae (Selenastrum capricornutum)	10 mg/l		
Environmental fate					
Biodegradation	Readily biode	egradable.			
13. DISPOSAL CONSIDERATIONS					

This material when discarded is not a hazardous waste as that term is defined by the US EPA RCRA Status: Resource, Conservation and Recovery Act (RCRA), 40 CFR 261. Disposal considerations: Incineration Recycle Miscellaneous advice: This product meets the criteria for a synthetic used oil under the U.S. EPA Standards for the Management of Used Oil (40 CFR 279). Those standards govern recycling and disposal in lieu of 40 CFR 260 -272 of the Federal hazardous waste program in states that have adopted these used oil regulations. Consult your attorney or appropriate regulatory official to be sure these standards have been adopted in your state. Recycle or burn in accordance with the applicable standards. Local, state, provincial, and national disposal regulations may be more or less stringent. This product should not be dumped, spilled, rinsed or washed into sewers or public waterways.

14. TRANSPORT INFORMATION

The data provided in this section is for information only. Please apply the appropriate regulations to properly classify your shipment for transportation.

US DOT Other:	Not regulated for transport.		
<u>Canadian TDG</u> Other:	Not regulated for transport.		
ICAO/IATA Class			

15. REGULATORY INFORMATION

Other:

All components are in compliance with the following inventories:	U.S. TSCA, EU EINECS, Canadian DSL, Australian AICS, Korean, Japanese ENCS, Chinese
Canadian WHMIS classification:	D2(B) - Materials Causing Other Toxic Effects
SARA Hazard Notification:	
Hazard Categories Under Title III Rules (40 CFR 370):	Immediate Delayed
Section 302 Extremely Hazardous	Not applicable

Not regulated for transport.

Substances:

Section 313 Toxic Chemical(s): Not applicable

CERCLA Reportable Quantity:

Not applicable

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation and the MSDS contains all the information required by the Canadian Controlled Products Regulation.

Refer to Section 11 for OSHA/HPA Hazardous Chemical(s) and Section 13 for RCRA classification.

Safety data sheet also created in accordance with Brazilian law NBR 14725

16. OTHER INFORMATION

Product use:	Hydraulic fluids and additives				
Reason for revision:	Significant changes to the following section(s):, Section 3				
Suggested NFPA Rating Suggested HMIS Rating:	Health 2 2	Fire 1 1	Reactivity 0 0	Additional Information	

Prepared by the Solutia Hazard Communication Group. Please consult Solutia @ 314-674-6661 if further information is needed.

TM, ® is a registered trademark of Solutia Inc. SOLUTIA is a trademark of Solutia Inc. Responsible Care® is a registered trademark of the American Chemistry Council.

Although the information and recommendations set forth herein (hereinafter "Information") are presented in good faith and believed to be correct as of the date hereof, Solutia Inc. makes no representations as to the completeness or accuracy thereof. Information is supplied upon the condition that the persons receiving same will make their own determination as to its suitability for their purposes prior to use. In no event will Solutia Inc. be responsible for damages of any nature whatsoever resulting from the use of or reliance upon Information. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS.