




## **Heavy-Duty Vinyl Tape**



**Backing:** PVC Film

Adhesive: Acrylic (A272)

Liner: 53# Coated Kraft Paper

Colors: Black

Specifications: A-A-1689B, Type II (supersedes PPP-T-66E, Type 1,

Class II)

**Size Options:** Incremental sizes 1/4" - 54" x 100Ft

## **Applications**

 Provides maximum masking protection during media blast or shot peening applications

- Gasketing material
- Abrasion protection

## Features Benefits

PVC Film Backing	Conformable to irregular surfaces		
	<ul> <li>Durable and abrasion resistant</li> </ul>		
Acrylic Adhesive	Aggressive long-term bond		
	<ul> <li>Low residue upon removal</li> </ul>		
	<ul> <li>Excellent low temperature performance</li> </ul>		
Paper Release Liner	Die-cuttable		
	Easy to apply		

## **Typical Test Values**

	Standard UOM		Metric UOM		Test Method
Total Thickness	9.5	mils	0.241	mm	PSTC-133
Substrate Thickness	8.5	mils	0.216	mm	PSTC-133
Adhesion to Steel	50	oz/in	5.47	N/cm	ASTM D-3330
Tensile Strength	25	lb/in	43.78	N/cm	ASTM D-3759
Elongation	160%				
WVTR	1.52 g/100in <sup>2</sup> /day			ASTM D-3833	
Abrasion Index	34				ASTM D-4060
Application Temperature	50 to 120 °F		10 to 49 °C		
Operating Temperature	-40 to 200 °F		-40 to 93 °C		

Recommended Storage Conditions: 40-60% Humidity, 60°F-80°F Standard Shelf Life (at 25 °C): 12 months from shipment date

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.

