





cking:	Embossed Polypropylene			
hesive:	Pigmented Polyurethane (U515)			
er:	N/A			
lors:	Green			
ecifications:	N/A			
e Options:	Incremental sizes 1/8" - 48" x 180Ft			

Applications

 Automotive OEM and aftermarket fineline masking

• Masking color separations on plastic, aluminum, steel, and fiberglass

	Features	Benefits				
•	Embossed Polypropylene Backing	Conformable				
		Solvent resistant				
		 Transparent for easy application 				
٠	Polyurethane Adhesive	Good all temperature performance				
		 Holds up to many paint systems 				
		Excellent surface wetability				
•	Clean-cut Plastic Core	Splinter & fiber free for less surface contamination				

Typical Test Values

	51				
Standard UOM		Metric UOM		Test Method	
5.0	mils	0.127	mm	PSTC-133	
3.5	mils	0.089	mm	PSTC-133	
30	oz/in	3.28	N/cm	ASTM D-3330	
13	lb/in	22.77	N/cm	ASTM D-3759	
700%					
50 to 120 °F		10 to 4	49 °C		
-40 to 250 °F		-40 to	121 °C		
	5.0 3.5 30 13 700% 50 to	Standard UOM 5.0 mils 3.5 mils 30 oz/in 13 lb/in 700% 50 to 120 °F	Standard UOM Metric 5.0 mils 0.127 3.5 mils 0.089 30 oz/in 3.28 13 lb/in 22.77 700% 50 to 120 °F 10 to 4	Standard UOM Metric UOM 5.0 mils 0.127 mm 3.5 mils 0.089 mm 30 oz/in 3.28 N/cm 13 lb/in 22.77 N/cm 700% 50 to 120 °F 10 to 49 °C	Standard UOM Metric UOM Test Method 5.0 mils 0.127 mm PSTC-133 3.5 mils 0.089 mm PSTC-133 30 oz/in 3.28 N/cm ASTM D-3330 13 lb/in 22.77 N/cm ASTM D-3759 700% 50 to 120 °F 10 to 49 °C 10 to 49 °C

Recommended Storage Conditions: 40-60% Humidity, 60 - 80 °F Standard Shelf Life (at 25 °C): 12 months from shipment date

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Global's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.



25 Forge Pkwy Franklin, MA 02038 1-800-343-7875 Fax 1-800-328-4822 www.berryglobal.com 1/31/18