



Heavy-Duty Outdoor Surface Protection Tape

Backing Adhesive	Backing:	Exterior-Grade Aliphatic Polyurethane		
Liner	Adhesive:	Acrylic (A106)		
	Liner:	94# Coated Kraft Paper		
	Colors:	Transparent		
	Specifications:	N/A		
Single Coated w/Liner	Size Options:	Incremental sizes 1/4" - 48" x 108Ft		
Applications				
 Surface protection on high-wear surfaces prone to scratching, chipping, and weathering Leading edge protection for wind turbine blades 		Protects leading edges of aircraft wings, stabilizers, or struts Surface protection for air foil and ground effects panels on racing cars and trucks		
Features		Benefits		
Features		Benefits		
Polyurethane Film Backing	•	Non-yellowing for long term applications Abrasion and UV resistant Printable and paintable Conformable for curves and irregular surfaces		
	•	Non-yellowing for long term applications Abrasion and UV resistant Printable and paintable		
Polyurethane Film Backing	• • • •	Non-yellowing for long term applications Abrasion and UV resistant Printable and paintable Conformable for curves and irregular surfaces Transparent for easy inspection High strength bond to smooth or irregular surfaces		
 Polyurethane Film Backing Acrylic Adhesive 	• • • •	Non-yellowing for long term applications Abrasion and UV resistant Printable and paintable Conformable for curves and irregular surfaces Transparent for easy inspection High strength bond to smooth or irregular surfaces Will not dry out, lift, or stain Smooth clean release - easy to use Die cuttable		
 Polyurethane Film Backing Acrylic Adhesive 	Typical Tes	Non-yellowing for long term applications Abrasion and UV resistant Printable and paintable Conformable for curves and irregular surfaces Transparent for easy inspection High strength bond to smooth or irregular surfaces Will not dry out, lift, or stain Smooth clean release - easy to use Die cuttable		
 Polyurethane Film Backing Acrylic Adhesive 	• • • • • • • • • • • • • • • • • • •	Non-yellowing for long term applications Abrasion and UV resistant Printable and paintable Conformable for curves and irregular surfaces Transparent for easy inspection High strength bond to smooth or irregular surfaces Will not dry out, lift, or stain Smooth clean release - easy to use Die cuttable		
 Polyurethane Film Backing Acrylic Adhesive Kraft Paper Release Liner 	Typical Tes Standard UOM Met 14.5 mils 0.	Non-yellowing for long term applications Abrasion and UV resistant Printable and paintable Conformable for curves and irregular surfaces Transparent for easy inspection High strength bond to smooth or irregular surfaces Will not dry out, lift, or stain Smooth clean release - easy to use Die cuttable t Values ric UOM Test Method		
 Polyurethane Film Backing Acrylic Adhesive Kraft Paper Release Liner Total Thickness	Typical Test Standard UOM Met 14.5 mils 0. 12.0 mils 0.	Non-yellowing for long term applications Abrasion and UV resistant Printable and paintable Conformable for curves and irregular surfaces Transparent for easy inspection High strength bond to smooth or irregular surfaces Will not dry out, lift, or stain Smooth clean release - easy to use Die cuttable t Values ric UOM Test Method 368 mm PSTC-133		

Tensile Strength	80 lb/in	140.10 N/cm	ASTM D-3759
Puncture Resistance	40 lbs	4.99 kg	ASTM D-1000
Elongation	500%		
Film Hardness (Shore A)	80		ASTM D-2240
Weight	12.5 oz/yd ²	423.82 g/m ²	
Application Temperature	50 to 120 °F	10 to 49 °C	
Operating Temperature	-40 to 275 °F	-40 to 135 °C	

Recommended Storage Conditions: 40-60% Humidity, 60 - 80 °F Standard Shelf Life (at 25 °C): 12 months from shipment date

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical, personnel. To BERRY GLOBAL'S knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.

